User Manual

ARK for Windows Enterprise (ARKWE)

Admin Report Kit for Windows Enterprise
ARKWE
Copyright (c) 1999 - 2014 Vyapin Software Systems Private Limited. All Rights Reserved.
Email: support@vyapin.com Web: www.vyapin.com

Last Updated: January 2015

Copyright © 2015 Vyapin Software Systems Private Ltd. All rights reserved.

This document is being furnished by Vyapin Software Systems Private Ltd for information purposes only to licensed users of the ARKWE software product and is furnished on an “AS IS” basis, that is, without any warranties, whatsoever, express or implied. ARKWE is a trademark of Vyapin Software Systems Private Ltd. Information in this document is subject to change without notice and does not represent any commitment on the part of Vyapin Software Systems Private Ltd. The software described in this document is furnished under a license agreement. The software may be used only in accordance with the terms of that license agreement. It is against the law to copy or use the software except as specifically allowed in that license. No part of this document may be reproduced or retransmitted in any form or by any means, whether electronically or mechanically, including, but not limited to the way of: photocopying, recording, or information recording and retrieval systems, without the express written permission of Vyapin Software Systems Private Ltd.

Vyapin Software Systems Private Limited

Website: http://www.vyapin.com/
Sales Contact: sales@vyapin.com
Technical Support: support@vyapin.com

Table of Contents

1 General Information 1

1.1 About Admin Report Kit for Windows Enterprise (ARKWE) 1

1.2 System Requirements 2

1.3 Who Can Use ARKWE? 3

1.4 How to Activate the Software? 4

1.5 Technical Support 6

2 Getting Started 7

2.1 Configuration Wizard 7

Configuration Settings 13

2.1.1 Database Settings 13

2.1.2 Computer Enumeration 15

2.1.3 Configuring Domain Credentials 16

2.1.4 Add a Domain/Server 19

2.1.5 Edit a Domain/Server 21

2.1.6 Delete a Domain/Server 23

2.1.7 Add Domains from Forest 24

2.1.8 Configure SMTP Server 27

2.1.9 User Connection Profiles 28

3 Standard Reports 30

3.1 How to View Domain Information? 30

3.2 How to View Shares and Resources Information? 33

3.3 How to View Users and Groups Information? 37

3.4 How to View Policies Information? 41

3.5 How to View Events Information? 46

3.6 How to View Service Information? 49

4 Built-in Reports 51

4.1 About Built-in Reports 51

4.2 How to View Built-in Permissions Reports? 51

4.3 How to View Built-in Reports for Shares and Resources? 67

4.4 How to View Built-in Reports for Users and Groups? 71

4.5 How to View Built-in Reports for Domains? 75

5 System Information 79

5.1 About System Info 79

5.2 How to View Network Configuration Reports? 81

5.3 How to View Operating System & Hot Fixes Reports? 84

5.4 How to View Printer Configuration Reports? 86

5.5 How to View Hardware Configuration Reports? 87

5.6 How to View Display Configuration Reports? 90

5.7 How to View Internet Explorer Configuration Reports? 92

5.8 How to View Current Status Reports? 93

5.9 How to View Environment Info Reports? 94

6 Additional Features 95

6.1 How to customize fields? 95

6.2 How to Apply Filters? 96

6.3 How to Refresh Data? 98

6.4 How to Export Data? 98

6.5 How to E-mail Data? 100

6.6 How to Find Data in a Report? 104

6.7 How to Scan Specific Servers in a Domain? 106

7 Power Export 109

7.1 About Power Export 109

7.2 Task Manager-Scheduled Tasks Manager 110

7.3 Schedule Standard Reports 112

7.4 Schedule Built-in Reports 123

7.5 Schedule Shares and Resources Built-in Reports 150

7.6 Schedule Users and Groups Built-in Reports 160

7.7 Schedule Domain Built-in Reports 169

8 Scan Profiles Manager 179

8.1 About Scan Profiles (Computers) 179

8.2 How to Create Scan Profiles (Computers)? 180

8.3 How to Manage Scan Profiles (Computers)? 185

8.4 How to Apply Scan Profiles (Computers)? 187

8.5 About Scan Profiles (Users/Groups) 189

8.6 How to Create Scan Profiles (Users/Groups)? 189

8.7 How to Manage Scan Profiles (Users/Groups)? 193

8.8 How to Apply Scan Profiles (Users/Groups)? 195

8.9 About Scan Profiles (Shares) 199

8.10 How to Create Scan Profiles (Shares)? 199

8.11 How to Manage Scan Profiles (Shares)? 202

8.12 How to Apply Scan Profiles (Shares)? 204

References 208

8.13 Troubleshooting 208

8.14 How to Uninstall ARKWE? 209

9 Index 213

Chapter 1

1 General Information

1.1 About Admin Report Kit for Windows Enterprise (ARKWE)

Admin Report Kit for Windows Enterprise (ARKWE) is a powerful reporting solution for the Microsoft Windows Network. ARKWE collects configuration information about Windows domains & servers, users/groups, policies, events, services, installed applications, shares, permissions, printers, data sources etc. The reports are presented in a variety of formats that are simple, elegant and highly customizable for System Administrators, IT infrastructure Managers and Systems Audit personnel to use and act on. ARKWE's basket of Built-in reports provides powerful, ready-to-use reports that assist in both Management reporting and Compliance reporting requirements such as SOX and HIPPA. A single solution that serves your everyday needs of administrative tasks as well as complex data preparation tasks for assisting in compliance.

ARKWE has been architected using the latest Microsoft .NET technology, bringing you the best-in-breed reporting solution for your entire Windows Network. ARKWE is highly optimized for performance (using native Windows API calls wherever appropriate), resulting in fast data collection of deeply embedded configuration data. Imagine scanning your vast network of workstations and servers without having to wait forever to see your reports! You can create data subsets for your network using our powerful scan options and meaningfully segment your entire network for data collection and reporting.

ARKWE supports current versions of Microsoft Windows Server (2000/2003/2008/2012) and localized versions of Windows Server, including German, Spanish and French.

1.2 System Requirements

For the computer running ARKWE

Processor:	Intel Pentium Processor
Disk Space & Memory:	512 MB RAM and minimum of 20 MB of free disk space.
Operating System:	Windows 8 / Windows 7 / Windows Vista / Windows XP / Windows Server 2012 / Windows Server 2008 R2 / Windows Server 2008 / Windows Server 2003 / Windows Server 2000 with .NET Framework 4.0 or higher with the latest service packs.
Database:	Microsoft SQL Server 2008 (Enterprise / Standard / Developer / Express edition) or Microsoft SQL Server 2005 (Enterprise / Standard / Developer / Express edition) running in local / remote computer with latest Service Pack.
Software:	MDAC v2.5/2.6/2.8

For the Computers Reported by ARKWE

Windows 8 / Windows 7 / Windows Vista / Windows XP / Windows Server 2012 / Windows Server 2008 R2/ Windows Server 2008 / Windows 2003 / Windows 2000 with Microsoft Remote Registry Service enabled.

1.3 Who Can Use ARKWE?

Organizations running Microsoft Windows Servers can greatly benefit from ARKWE. It is a powerful reporting tool for Windows Server Administrators. System Administrators can monitor and manage Microsoft Windows Servers across the enterprise network in any location. You can connect to a Windows Server if you are part of global administrator's group.

Typical Users

- Systems management personnel
- System Administrators
- Other Windows network product developers
- Trainers and educators
- Enterprise network planning personnel

Typical Organizations that would benefit from this Product:

- Companies having their LAN/WAN based Windows Enterprise Networks
- Windows based data warehousing companies
- Windows Server based Internet Service Providers
- Companies having Windows based Intranets
- Any company having Windows Servers and planning to manage their systems

1.4 How to Activate the Software?

Once you purchase the software online or through any one of our resellers, you will receive a sale notification through e-mail from our sales department. We will send you an e-mail with the necessary instructions to activate the software.

In case you do not receive an e-mail from our sales team after you purchase the software, please send the following information to our sales department at sales@vyapin.com with the sales order number:

- **Company Name:** End-user Company Name
- **Location:** City & Country for the Company Name given above

Please allow 12 to 24 hours from the time of purchase for our sales department to process your orders.


Activate Admin Report Kit for Windows Enterprise
License Type: 15-day Evaluation Copy
To activate the software, copy and paste the license key in the textbox below:
Click here to see how to copy and paste the license key
License Key
Activate
Cancel

Image 1 - Activate screen

Perform the following steps to activate the software:

1) Download evaluation/trial copy of software from the respective product page available in our website at http://www.vyapin.com/

2) Install the software on the desired computer.

3) You will receive a license key through e-mail as soon as the purchase process is complete.

4) Click 'Activate' in Help -> About -> Activate menu to see the Activate dialog (as shown in Image 1).

5) Copy the license key sent to you through email, and pastes it in the 'License Key' textbox. For help on how to copy the license key, click 'Click here to see how to copy and paste the license key' link in the Activate dialog (as shown in Image 2).



Image 2 - How to copy license key screen

1.5 Technical Support

ARKWE Frequently Asked Questions (FAQ) section is available online at our website http://www.vyapin.com.

Please direct all technical support questions to support@vyapin.com. Include the following information to expedite a response:

a) Include the version of the product you are using.
b) If the problem is associated with installation, include the steps that led to the problem.
c) If the problem is associated with usage, please state the series of steps you performed.
d) Include the version of the OS, info about any service packs or hot-fixes and local language of the OS installed.
e) Attach the Error Log File available in the common application data path of ARKWE (e.g., <Application Data Folder> \ARKWE 8x\ARKWEErrorLog.log).

NOTE:

<Application Data Folder> is the common area where ARKWE settings will be stored in the machine running ARKWE. The <Application Data Folder> can be found from the Help -> About screen. The default path of <Application Data Folder> is as follows:

a) Windows XP Windows 2003**-**C:\Documents and Settings\All Users\Documents
b) Windows Vista, Windows 7, Windows 8, Windows 2008, Windows Server 2012 - C:\Users\Public\Documents

2 Getting Started

2.1 Configuration Wizard

Configure ARKWE

There are two ways to configure ARKWE - one through the configuration wizard and the other by directly modifying the specific configuration settings.

Using ARKWE Configuration Wizard

ARKWE configuration wizard will help you configure the application during the startup of the first run. You can access the wizard anytime by choosing **Tools** > **Configuration Wizard** from the main application menu.


ARKWE Configuration Wizard
Welcome to ARKWE configuration wizard. The wizard will guide you through the process of configuring ARKWE.
This wizard allows you to configure the following:
1. Database Settings
2. Computer Enumeration
3. Domain Credentials
Show at startup
< Back
Next >
Finish
Close

Click **Next** to proceed.

Step 1 of 3: Database Settings


Configuration Settings
Database Settings
Select an option for storing the application data either in MS Access or SQL server. If you choose SQL server, enter a SQL server running SQL Server 2005 / 2008 /2012 (Enterprise / Standard / Express) edition and the user credential having sufficient privileges to connect, create and delete database in the specified SQL server.
Settings
Database Settings
Computer Enumeration
Domain Credentials
E-mail Settings
User Connection Profil
Use MS Access
Use SQL Server
SQL Server: RD28
e.g., MSSQLSRV1
Database Option
Use a single central database for all instances of the application
Use a separate database for each instance of the application
Authentication Mode:
Windows Authentication (Currently logged on user)
SQL Server Authentication
User Name: sqllogin3
Password: ••••••••••
OK
Cancel

ARKWE may be configured to use either MS-Access MDB or SQL Server database for its data storage to generate reports. If you choose SQL server, ARKWE requires an SQL Server running SQL Server 2012 / 2008 / 2005 (Enterprise / Standard / Express editions) to connect and create a database. ARKWE will connect to the specified SQL Server based on the authentication mode and the user credentials to create and manage its own application databases. Database will be created in the specified SQL server based on the following database options (whichever is selected):

1) Use a single central database for all instances of the application

- A new database will be created in the SQL server by the name ARKWE. Inside the ARKWE database, separate tables will be created for each installation of ARKWE. The table names will be prefixed with the computer name that is running ARKWE application. Thus, each installation of ARKWE will deploy its own tables based on the computer where ARKWE is installed. For example, if you install the software on 3 different computers, single database with 3 different tables will be created inside the single database and each installed application will generate reports separately independent of each other.

2) Use a separate database for each instance of the application

- A new database will be created in the SQL server by the name ARKWE-<COMPUTERNAME>, where COMPUTERNAME stands for the computer name that is running ARKWE application. Thus, each installation of ARKWE will deploy its own database based on the computer where ARKWE is installed. For example, if you install the software on 3 different computers, 3 different databases will be created and each installed application will generate reports separately independent of each other.

Specify the SQL Server name, authentication mode, user name and password in the above screen.

Click **Next** to proceed.

Step 2 of 3: Computer Enumeration

ARKWE uses Computer Browser Services or Active Directory services for enumerating computers in your domain. In order to automatically enumerate computers in your network, the application may be configured to use either the Computer Browser Service (uses Windows Network APIs) or your Active Directory (queries your AD for Computer Accounts).

1) Use Computer Browser Service

- Uses Windows Network API to enumerate computers in a domain. This displays all the computers that are currently active in your Network. This option may be used if you have a small network for faster enumeration of computers.

2) Use Active Directory Services

- Queries your Directory Server to enumerate its computers. This option requires Domain Administrator credentials to connect to your domain controller.


ARKWE Configuration Wizard
Step 2 of 3 : Computer Enumeration
Select an option for enumerating computers in your domain. In order to automatically enumerate computers in your network, the application may be configured to use either the Computer Browser Service (uses Windows Network APIs) or your Active Directory (queries your AD for Computer Accounts).
Use Computer Browser Service
Uses Windows Network API to enumerate computers in a domain. This displays all the computers that are currently active in your Network. This option may be used if you have a small network for faster enumeration of computers.
Use Active Directory Services
Queries your Directory Server to enumerate its computers. This option requires Domain Administrator privilege to connect to your domain controller.
Show at startup
< Back
Next >
Finish
Close

Click **Next** to Proceed.

Step 3 of 3: Domain Credentials

Manage alternate credentials for Domain / Directory Servers. The application by default uses the currently logged on user context to enumerate computers, shares and to collect report data. If you want to specify alternate Domain Administrator credentials you may do so by clicking on the 'Add ' button below. Click 'Add domains from forest' option to enumerate domains from a different forest and then supply necessary credentials for the selected domain.


ARKWE Configuration Wizard
Step 3 of 3 : Domain Credentials
Manage alternate credentials for Domain / Directory Servers. Specify an account name that has admin privileges to the selected domain. The specified credentials will be used to connect to all computers in the domain to retrieve report information. If you want to specify alternate Domain Administrator credentials you may do so by clicking on the 'Add' button below. Click 'Add domains from forest' option to enumerate domains from a different forest and then supply necessary credentials for the selected domain.
Add
Edit
Delete
Connect
Add domains from forest...
Domain/Server Name
Forest Name
User Name
Status
RD83
HULK
RD83\Administrator
Connected
Researchlab
researchlab.local
Researchlab\adminuser3
Connected
voyager
Voyager.local
voyager\adminuser3
Connected
Show at startup
< Back
Next >
Finish
Close

For more information on Domain Credentials please refer Domain Credentials. Click Finish to save the configuration details.

Using the Configuration Settings Dialog

You may directly modify the configuration settings, once you get familiar with the user interface. You may access the Configuration Settings menu from the Tools menu in the application. Once you open the Settings window, you will see the different modules for configuration.


Configuration Settings
Domain Credentials
Manage alternate credentials for Domain / Directory Servers. Specify an account name that has admin privileges to the selected domain. The specified credentials will be used to connect to all computers in the domain to retrieve report information. If you want to specify alternate Domain Administrator credentials you may do so by clicking on the 'Add' button below. Click 'Add domains from forest' option to enumerate domains from a different forest and then supply necessary credentials for the selected domain.
Settings
Database Settings
Computer Enumeration
Domain Credentials
E-mail Settings
User Connection Profil
Add
Edit
Delete
Connect
Add domains from forest...
Domain/Server Name
Forest Name
User Name
Status
RD83
HULK
RD83\Administrator
Connected
Researchlab
researchlab.local
Researchlab\adminu
Connected
voyager
Voyager.local
voyager\adminuser3
Connected
Close

Configuration Settings

2.1.1 Database Settings

ARKWE may be configured to use either MS-Access MDB or SQL Server database for its data storage to generate reports. If you choose SQL server ARKWE requires an SQL Server running SQL Server 2005 / 2008 / 2012 (Enterprise / Standard / Express editions) to connect and create a new application database. ARKWE will connect to the specified SQL Server based on authentication mode and user credentials to manage its own application database.

You can access the Database settings by clicking Tools -> Configuration Settings menu in the ARKWE main application window and choose Database settings, as shown below:


Configuration Settings
Database Settings
Select an option for storing the application data either in MS Access or SQL server. If you choose SQL server, enter a SQL server running SQL Server 2005 / 2008 /2012 (Enterprise / Standard / Express) edition and the user credential having sufficient privileges to connect, create and delete database in the specified SQL server.
Settings
Database Settings
Computer Enumeration
Domain Credentials
E-mail Settings
User Connection Profil
Use MS Access
Use SQL Server
SQL Server: RD28
e.g., MSSQLSRV1
Database Option
Use a single central database for all instances of the application
Use a separate database for each instance of the application
Authentication Mode:
Windows Authentication (Currently logged on user)
SQL Server Authentication
User Name: sqllogin3
Password: ••••••••••
OK
Cancel

User Authentication

To connect to SQL Server, ARKWE uses the relevant user accounts based on the authentication mode as listed below:

A. Windows Authentication:

In this method, ARKWE uses the currently logged on user account while running reports

B. SQL Authentication:

In this method, ARKWE uses the specified SQL user account and password while running reports. ARKWE stores the SQL user name and password as a user profile in 'Stored User Names and Passwords' applet for its usage.

Note: ARKWE expects the user account to have sufficient privileges to create, add to and delete database in the SQL server.

Database Creation

ARKWE creates databases in SQL Server based on the following database options (whichever is selected) as outlined below:

1) Use a single central database for all instances of the application

- A new database will be created in the SQL server by the name ARKWE. Inside the ARKWE database, separate tables will be created for each installation of ARKWE. The table names will be prefixed with the computer name that is running ARKWE application. Thus, each installation of ARKWE will deploy its own tables based on the computer where ARKWE is installed. For example, if you install the software on 3 different computers, single database with 3 different tables will be created inside the single database and each installed application will generate reports separately independent of each other.

2) Use a separate database for each instance of the application

- ARKWE creates a single application database in the default data storage location used by the SQL Server during application launch. ARKWE uses the following naming convention: ARKWE-<COMPUTERNAME>, where COMPUTERNAME is the name of the computer running ARKWE.
- For example, if the computer running ARKWE is 'CLIENT01', ARKWE creates 'ARKWE-CLIENT01' with data ('ARKWE-CLIENT01.mdf') and log (''ARKWE-CLIENT01_log.LDF') files stored in the default SQL data folder in the SQL server (for example, C:\Program Files\Microsoft SQL Server\MSSQL.1\MSSQL\Data).

Database Cleanup

ARKWE will delete the application database while uninstalling the ARKWE application from the computer.

2.1.2 Computer Enumeration

Configure Computer Enumeration

For enumerating computers in your network automatically, ARKWE uses either Computer Browser Service or Active Directory Services. Select an option for enumerating computers in your domain as shown below. You may use the Browser service if you have a smaller network, as it may take time for the Browser service to respond to data requests on large networks. The advantage of a Browser service is that it lists only those computers that are currently active or alive on your network. You may use the Active Directory Services option if you have a large network and you need a quicker enumeration of computers in your domain. However, this option requires that the domain controller is contacted and queried. Therefore, the currently logged on user must have sufficient privileges to connect to a domain controller or you may specify alternate domain credentials for a domain controller (see configuring the Domain Credentials section in the wizard).

NOTE: IF you use the Browser service, ensure that NETBIOS over TCP/IP is enabled in both the client and the computers that need to be reported on. The Browser service must also be running.

You can access the Computer Enumeration settings by clicking Tools -> Configuration Settings menu in the ARKWE main application window and selecting "Computer Enumeration" node as shown below:


Configuration Settings
Computer Enumeration
Select an option for enumerating computers in your domain. In order to automatically enumerate computers in your network, the application may be configured to use either the Computer Browser Service (uses Windows Network APIs) or your Active Directory (queries your AD for Computer Accounts).
Settings
Database Settings
Computer Enumeration
Domain Credentials
E-mail Settings
User Connection Profil
Use Computer Browser Service
Uses Windows Network API to enumerate computers in a domain. This displays all the computers that are currently active in your Network. This option may be used if you have a small network for faster enumeration of computers.
Use Active Directory Services
Queries your Directory Server to enumerate its computers. This option requires Domain Administrator privilege to connect to your domain controller.
Close

2.1.3 Configuring Domain Credentials

Domain Credentials

Manage alternate credentials for Domain / Directory Servers. The application by default uses the currently logged on user context to enumerate computers, shares and to collect report data. If you want to specify alternate Domain Administrator credentials you may use this option.

Configuring Domain Credentials

You can access the Domain Credentials settings by selecting the Domain Credentials option in the Configuration Settings window.


Configuration Settings
Domain Credentials
Manage alternate credentials for Domain / Directory Servers. Specify an account name that has admin privileges to the selected domain. The specified credentials will be used to connect to all computers in the domain to retrieve report information. If you want to specify alternate Domain Administrator credentials you may do so by clicking on the 'Add' button below. Click 'Add domains from forest' option to enumerate domains from a different forest and then supply necessary credentials for the selected domain.
Settings
Database Settings
Computer Enumeration
Domain Credentials
E-mail Settings
User Connection Profil
Add
Edit
Delete
Connect
Add domains from forest...
Domain/Server Name
Forest Name
User Name
Status
Close

If you have chosen Active Directory Services under the Computer Enumeration settings, you can launch the ARKWE Domain Credentials window within a report window by doing the following:

1) Select any one of the reports from the ARKWE main application window. For example Standard Reports -> Domains-Shares option.

2) The action will launch the Domains-Shares report window.

3) In the report window, at the bottom of the treeview click **Add Domains** button. This action will launch the "**Domain Credentials**" window as shown below.





The various operations that can be performed in the Domain Credentials screen are given below:

Operation	Description
Add	To Add a new domain to the list.
Edit	To Edit the properties of a domain/server in the list. Select a domain/server and click Edit button.
Delete	To Delete a domain/server from the list. Select a domain/server and click Delete button.
Connect	To connect to a domain/server in the list. Select a domain/server and click Connect button.

2.1.4 Add a Domain/Server

You may also add one single domain or server at a time to the list of domains or servers in the credentials list by using Add Domain/Server feature.

Add a domain to the list

1) Launch Domain Credentials window.

2) In the Domain Credentials window, click **Add** button to add a domain/server to the list.

3) The New **Add domain/server** dialog will be displayed as shown below:


Add domain/server
Specify a Domain name to retrieve computers present in domain. Clear the 'Log on using current user' checkbox to specify alternate credentials for connecting to the domain or server.
Domain (or) Server Name:
Log on using current user
User Name:
phoenix\Administrator
Password:
Store the above credentials in Microsoft windows Stored User Name and Passwords applet
OK
Cancel

Enter the name of a domain or server.


Add domain/server
Specify a Domain name to retrieve computers present in domain. Clear the 'Log on using current user' checkbox to specify alternate credentials for connecting to the domain or server.
Domain (or) Server Name:
voyager
Log on using current user
User Name:
voyager\adminuser3
Password:
Store the above credentials in Microsoft windows Stored User Name and Passwords applet
OK
Cancel

4) Specify user name and the corresponding password to connect to the specified domain or server.

Store the above user credential in Microsoft Windows Stored User Names and Passwords applet - ARKWE allows the user to enter different user credentials to connect to the domain/server. Uncheck the checkbox 'Log on using current user' if you like to connect to the domain/server using a different user context.

ARKWE will store the user credential to connect to domain/server in the Microsoft Windows Stored User Names and Passwords applet / Credential Manager for security reasons. The stored user profile is tied to the user context (currently logged on user account) in which the profile is created.

5) Click OK to add the domain/server to the Domain Credentials list.

6) ARKWE will connect to the domain/server with the newly provided connection parameters and add it to the list, upon successful connection to the domain/server.


Configuration Settings
Domain Credentials
Manage alternate credentials for Domain / Directory Servers. Specify an account name that has admin privileges to the selected domain. The specified credentials will be used to connect to all computers in the domain to retrieve report information. If you want to specify alternate Domain Administrator credentials you may do so by clicking on the 'Add' button below. Click 'Add domains from forest' option to enumerate domains from a different forest and then supply necessary credentials for the selected domain.
Settings
Database Settings
Computer Enumeration
Domain Credentials
E-mail Settings
User Connection Profil
Add
Edit
Delete
Connect
Add domains from forest...
Domain/Server Name
Forest Name
User Name
Status
RD83
HULK
RD83\Administrator
Connected
Researchlab
researchlab.local
Researchlab\adminuse
Connected
voyager
Voyager.local
voyager\adminuser3
Connected
Close

7) Click Cancel to abort the add process of the domain/server to the Domain Credentials list.

2.1.5 Edit a Domain/Server

To Edit a domain/server in the Domain Credentials, follow the steps given below:

1) Launch Domain Credentials window.

2) In the Domain Credentials window, select any row (domain), Click **Edit** button to Edit an existing domain/server in the list, as shown below:


Configuration Settings
Domain Credentials
Manage alternate credentials for Domain / Directory Servers. Specify an account name that has admin privileges to the selected domain. The specified credentials will be used to connect to all computers in the domain to retrieve report information. If you want to specify alternate Domain Administrator credentials you may do so by clicking on the 'Add' button below. Click 'Add domains from forest' option to enumerate domains from a different forest and then supply necessary credentials for the selected domain.
Settings
Database Settings
Computer Enumeration
Domain Credentials
E-mail Settings
User Connection Profil
Add
Edit
Delete
Connect
Add domains from forest...
Domain/Server Name
Forest Name
User Name
Status
RD83
HULK
RD83\Administrator
Connected
Researchlab
researchlab.local
Researchlab\adminuse
Connected
voyager
Voyager.local
voyager\adminuser3
Connected
Close

3) The domain/server name cannot be modified during the edit operation.

4) Specify user name and the corresponding password to connect to the specified domain/server.

5) Click **OK** to save and connect to the domain/server with the newly provided connection parameters and update the domain/server in the Domain Credentials list.

6) ARKWE will connect to the domain/server with the newly provided connection parameters and modify it in the list, upon successful connection to the domain/server.


Configuration Settings
Domain Credentials
Manage alternate credentials for Domain / Directory Servers. Specify an account name that has admin privileges to the selected domain. The specified credentials will be used to connect to all computers in the domain to retrieve report information. If you want to specify alternate Domain Administrator credentials you may do so by clicking on the 'Add' button below. Click 'Add domains from forest' option to enumerate domains from a different forest and then supply necessary credentials for the selected domain.
Settings
Database Settings
Computer Enumeration
Domain Credentials
E-mail Settings
User Connection Profil
Add
Edit
Delete
Connect
Add domains from forest...
Domain/Server Name
Forest Name
User Name
Status
RD83
HULK
RD83\Administrator
Connected
Researchlab
researchlab.local
Researchlab\adminuse
Connected
voyager
Voyager.local
voyager\adminuser3
Connected
Close

7) Click **Cancel** to retain the existing connection parameters of the domain/server in the Domain Credentials list.

2.1.6 Delete a Domain/Server

Perform the following steps to delete a domain/server:

1) Launch Domain Credentials window.

2) In the Domain Credentials window, select any row (domain), click **Delete** button to delete the forest from the Domain Enumeration Manager list.


Configuration Settings
Domain Credentials
Manage alternate credentials for Domain / Directory Servers. Specify an account name that has admin privileges to the selected domain. The specified credentials will be used to connect to all computers in the domain to retrieve report information. If you want to specify alternate Domain Administrator credentials you may do so by clicking on the 'Add' button below. Click 'Add domains from forest' option to enumerate domains from a different forest and then supply necessary credentials for the selected domain.
Settings
Database Settings
Computer Enumeration
Domain Credentials
E-mail Settings
User Connection Profil
Add
Edit
Delete
Connect
Add domains from forest...
Domain/Server Name
Forest Name
User Name
Status
RD83
HULK
RD83\Administrator
Connected
Researchlab
researchlab.local
Researchlab\adminuse
Connected
voyager
Voyager.local
voyager\adminuser3
Connected
Close

3) An alert message asking for confirmation to delete the domain/server will be displayed as shown below:



4) Click **Yes** to delete the selected forest.

5) Click **No** to abort the delete process of the selected forest.

2.1.7 Add Domains from Forest

In order to connect to a different forest in your Active Directory and configure these domains for enumerating computers and generating reports on them, you may use the 'Add Domains from Forest' feature.

Add domains from forest to the list

1) Launch Domain Credentials window.

2) In the Domain Credentials window, click **to add** domains from forest button to add domains in the forest to the list.

3) The **Enumerate All domains in a forest** dialog will be displayed as shown below:


Enumerate all Domains in a forest
Specify a Forest Name. The Forest Name will be used to retrieve domains present in the forest. Clear the 'Log on using current user' checkbox to specify alternate credentials for connecting to the forest.
Forest Name:
Note: The DNS name you specify here must be visible from this computer.
(This computer must be able to resolve the specified DNS name)
Domains in forest ()
Log on using current user
Show Domains >>
User Name:
RD54\Administrator
Password:
Store the above credentials in Microsoft windows Stored User Name and Passwords applet
OK
Cancel

Enter the name of a forest.


Enumerate all Domains in a forest
Specify a Forest Name. The Forest Name will be used to retrieve domains present in the forest. Clear the 'Log on using current user' checkbox to specify alternate credentials for connecting to the forest.
Forest Name: pathfinder.local
Note: The DNS name you specify here must be visible from this computer.
(This computer must be able to resolve the specified DNS name)
Domains in forest ()
Log on using current user
Show Domains >>
User Name: adventure\adminuser
Password:
Store the above credentials in Microsoft windows Stored User Name and Passwords applet
OK
Cancel

4) Specify user name and the corresponding password to connect to the specified forest.

Store the above user credential in Microsoft Windows Stored User Names and Passwords applet - ARKWE allows the user to enter different user credentials to connect to the forest. Uncheck the checkbox 'Log on using current user' if you like to connect to the forest using a different user context.

ARKWE will store the user credential to connect to forest in the Microsoft Windows Stored User Names and Passwords applet / Credential Manager for security reasons. The stored user profile is tied to the user context (currently logged on user account) in which the profile is created.

5) Click 'Show Domains' button to add the domains in the specified forest to the list and select the desired domains in the list. Click OK to add the selected domains to the Domain Credentials list as shown below:


Enumerate all Domains in a forest
Specify a Forest Name. The Forest Name will be used to retrieve domains present in the forest. Clear the 'Log on using current user' checkbox to specify alternate credentials for connecting to the forest.
Forest Name: pathfinder.local
Note: The DNS name you specify here must be visible from this computer.
(This computer must be able to resolve the specified DNS name)
Log on using current user
Show Domains >>
User Name: Pathfinder\adminuser
Password:
Store the above credentials in Microsoft windows Stored User Name and Passwords applet
Domains in forest [pathfinder.local]
ADVENTURE
CONQUEROR
PATHFINDER
OK
Cancel

6) ARKWE will add the selected domains to the Domain Credentials list.


Configuration Settings
Domain Credentials
Manage alternate credentials for Domain / Directory Servers. The application by default uses the currently logged on user context to enumerate computers and shares and to collect NTFS permissions data. If you want to specify alternate Domain Administrator credentials you may do so by clicking on the 'Add ' button below. Click 'Add domains from forest' option to enumerate domains from a different forest and then supply necessary credentials for the selected domain.
Settings
Database Settings
Computer Enumeration
Domain Credentials
E-mail Settings
User Connection Profil
Add
Edit
Delete
Connect
Add domains from forest...
Domain Name
Forest Name
User Name
Status
adventure
Adventure.local
adventure\adminuser
Connected
pathfinder
pathfinder.local
Pathfinder\adminuser
Connected
Close

2.1.8 Configure SMTP Server

ARKWE provides the option to e-mail the reports generated. For e-mailing reports, ARKWE requires SMTP Server, From E-mail Address, To E-mail Addresses (recipients separated by semicolon) and the e-mail report format. ARKWE maintains a single SMTP Server and a From E-mail Address for use by all reports. You can specify a separate set of "To" e-mail addresses (recipients), e-mail report format, subject and body of the message for each report.

You can set SMTP Server and From Address by clicking Tools -> Configuration Settings menu in the ARKWE main application window, as shown below:


Configuration Settings
E-mail Settings
Specify the SMTP Server name and Sender (From) e-mail address to send the generated reports through e-mail.
Settings
Database Settings
Computer Enumeratior
Domain Credentials
E-mail Settings
User Connection Profil
An SMTP server is the server that is used for your outgoing e-mail.
SMTP Server:
rd45
When you send e-mail, your name will appear in the from of the outgoing message.Type your name as you would like it to appear.
From Address:
Alex E.Fring@pathfinder.local
E.x: someone@example.com
OK
Cancel

2.1.9 User Connection Profiles

ARKWE creates a user profile in **Windows Stored User Names and Passwords applet / Credential Manager**, in order to store the domain user context for enumerating servers using ADSI.

The stored user profile will be useful for generating reports using ARKWE under the following scenarios:

- Using an alternate user account to connect to the domain to retrieve servers using ADSI.
- Providing credentials that have sufficient rights to enumerate shares present in computers within a domain.

The stored user profile persists for all subsequent logon sessions on the same computer where ARKWE is installed. The stored user profiles are visible to the application under other logon sessions on the same computer.

The stored user profile created by ARKWE is restricted to the Windows User Profile context. If the Windows User Profile is maintained locally, ARKWE stored user profile is accessible only by the same user in the same computer. If the user who creates ARKWE stored user profile, has a Roaming user account in the enterprise, the ARKWE stored user profile can be accessed by the same user in any computer in the Windows enterprise.

The stored user profile is a generic credential of **Windows Stored User Names and Passwords applet / Credential Manager** and can be used by the application only. The credential information is stored securely in a *256 bit encrypted format* in **Windows Stored User Names and Passwords applet / Credential Manager.**

The stored user profile corresponding to the user account will be used by the application in order to connect to the domain, if 'Use ADSI' is selected in ARKWE Enumeration Settings.

Using the Connection Profile dialog shown below, new profile can be created and available profiles can be removed from the profiles list.



Click **Add** button to add a new profile and a dialog will appear as shown below:



Click **Edit** button in the Connection Profile dialog to *edit* available profiles.

Click **Remove** button in the Connection Profile dialog to *remove* available profiles.

Chapter 2

3 Standard Reports

3.1 How to View Domain Information?

Domain Summary Information

Click 

to view domain summary information for a domain.

The summary report lists information like computer's operating system, browsing capability, participation in LanMan networks, membership in Windows workgroups etc., for the server(s) in the domain.

NOTE: For information on restricting the domain scan for generating this report, please see '[How to scan specific servers in a domain?]'

The output would be displayed as shown below:



Domain Trust Information



Click to view the trusted and trusting domains for a given domain.



Domain Shares Information



Click to view the shares for a given domain.



Domain Application Information



Click to view the applications installed for a given domain.

NOTE: For information on restricting the domain scan for generating this report, please see How to scan specific servers in a domain?



3.2 How to View Shares and Resources Information?



Click to view the following information: ***Share Name, Path, User Name, Security, Maximum, and Comment***



How to View Permissions of Folders in a Share?



Click tab. The ***"Folders and Permissions"*** dialog appears.



You can view permissions of folder(s) in a share or for all the shares in the selected server by selecting "All shares" option or "Select share(s)" option respectively.

You can also optionally include the sub-folder(s) information by selecting the "Include sub-folders" option.

The sub-folder(s) having permissions identical as the parent folder would be shown in bold text with "Same as parent" in both User Name and Security fields in the report. If you do not want folders with identical permissions as the parent folder reported, then select, the "Do not display folders that have same permissions as the parent folder" option. This option will not report folders with identical permissions as the parent folder.

To view up to a certain level of sub-folders, select the "Traverse only 'n' level(s) of sub-folder in the share" option and specify a sub-folder level, where the levels are numbered as follows:

\\server\sharename\Level 1\Level 2\Level 3...

NOTE: The "Include sub-folders" option defaults to enumerating all the sub-folders unless you specify a sub-folder level in "Traverse only 'n' level(s) of sub-folder in the share" option.

NOTE: The "Do not display folders that have same permissions as the parent folder" option would be enabled by default.

The report would be displayed as shown below:



How to view permissions of files in a share?

Click 

tab. The "**Files and Permissions**" dialog appears.



You can view permissions of files in a share or for all the shares in the selected server by selecting "All shares" option or "Select share(s)" option respectively.

You can also optionally include the sub-folder(s) information by selecting the "Include sub-folders" option.

The files having permissions identical to the parent folder would show up with "Same as parent" in both User Name and Security fields in the report. If you do not want files with identical permissions as the parent folder reported, then select, the "Do not display files that have same permissions as the parent folder" option. This option will not report files with identical permissions as the parent folder.

To view up to a certain level of sub-folders and files, select the "Traverse only 'n' level(s) of sub-folder in the share" option and specify a sub-folder level, where the levels are numbered as follows:

\\server\sharename\Level 1\Level 2\Level 3...

NOTE: The "Include sub-folders" option defaults to enumerating all the sub-folders unless you specify a sub-folder level in "Traverse only 'n' level(s) of sub-folder in the share" option.

NOTE: The "Do not display files that have same permissions as the parent folder" option would be enabled by default.

The report would be displayed as shown below:



3.3 How to View Users and Groups Information?



Click on to view the following information: ***User Name, Full Name, Description, Home Path, Logon Script*, and *User Profile Path.***





Click on to view the following information: ***User Name, Full Name, Description, Account Expiry, Password Editable, Password Age, Account Locked, and Account Disabled.***



Click on  to view the following information: ***User Name, Logon Machines, Last Logon.***





Click on to view the following information: ***Displays privilege lists on a per-user and per-privilege basis.***





Click on to view the following information: ***Displays group lists on a per-user and per-group basis.***





Click on to view the following information: ***Displays group member's lists on a per-group basis***



3.4 How to View Policies Information?



Click to view the following information: ***Enforce Password History, Maximum Password Age, Minimum Password Age, Minimum Password Length; Password must meet complexity requirements, Store password using reversible encryption for all domain users***





Click tab to view the following information: ***Account Lockout Duration, Account Lockout Threshold, and Reset Account Lockout***





Click to view the following information: ***Policy Name, Log Success, and Log Failure***





Click to view the following information: ***Privilege, Account Name***





Click to view the following information: ***Policy Name, Value***





Click to view the following information: ***Policy Name, Description, Policy Assigned, and Last Modified***


Policies - Security Options (RD40)
Refresh
Export
Filter
Customize
Scan Profiles (Computers)
E-mail
Find
Enterprise - POLI
RD83
RESEARCHLAB
VOYAGER
Domain Cont
RD40
Servers
RD41
RD43
Workstations
RD71
RD72
RD73
RD83
RD84
RD85
Add Domains
Password
Account Lockout
Audit
User Rights Assignment
Security Options
IP Security
Generated on: 29 Dec, 2014, 06:41:37 PM
Status: Success
Filter: Not Applied
Policy Name
Description
Policy Assigned
Last Modified
Server (Request Security)
For all IP traffic, always request security using Kerberos trust. Allow unsecured communication with clients that do not respond to request.
No
8/2/2012 6:46:12 PM
Client (Respond Only)
Communicate normally (unsecured). Use the default response rule to negotiate with servers that request security. Only the requested protocol and port traffic with that server is secured.
No
8/2/2012 6:46:12 PM
Secure Server (Require Security)
For all IP traffic, always require security using Kerberos trust. Do NOT allow unsecured communication with untrusted clients.
No
8/2/2012 6:46:12 PM

3.5 How to View Events Information?



Click to view the following information:

Event Date, Event Time, Description, Source Name, Event End, Computer Name, User Name, Event Type, and Category





Click to view the following information:

Event Date, Event Time, Description, Source Name, Event End, Computer Name, User Name, Event Type, and Category





Click to view the following information: ***Event Date, Event Time, Description, Source Name, Event End, Computer Name, User Name, Event Type, and Category***





Click to view the following information:

Opens the saved log stored in current system or network share.

3.6 How to View Service Information?



Click to view the following information:

Display Name, Start up, Service Type, Account, and Current State


Services - General (RD40)
Refresh
Export
Filter
Customize
Scan Profiles (Computers)
E-mail
Find
Enterprise - SERVICES
RD83
RESEARCHLAB
VOYAGER
Domain Controllers
RD40
Servers
RD41
RD43
Workstations
RD71
RD72
RD73
RD83
RD84
RD85
Add Domains
General
Control
Dependency
Generated on: 29 Dec, 2014, 06:57:23 PM
Status: Success
Filter: Not Applied
Display Name
StartUp
Service Type
Account
Current State
Cryptographic Services Auto Share Process NT Authority\NetworkService Running
DNS Client Auto Share Process NT AUTHORITY\NetworkService Running
KDC Proxy Server service (KPS) Manual Share Process NT AUTHORITY\NetworkService Stopped
KtmRm for Distributed Transaction Coordinator Manual Share Process NT AUTHORITY\NetworkService Stopped
Workstation Auto Share Process NT AUTHORITY\NetworkService Running
Distributed Transaction Coordinator Auto Own Process NT AUTHORITY\NetworkService Running
Network Access Protection Agent Manual Share Process NT AUTHORITY\NetworkService Stopped
Network Location Awareness Auto Share Process NT AUTHORITY\NetworkService Running
IPsec Policy Agent Manual Share Process NT Authority\NetworkService Running
RPC Endpoint Mapper Auto Share Process NT AUTHORITY\NetworkService Running
Remote Procedure Call (RPC) Locator Manual Own Process NT AUTHORITY\NetworkService Stopped
Remote Procedure Call (RPC) Auto Share Process NT AUTHORITY\NetworkService Running
Software Protection Auto Own Process NT AUTHORITY\NetworkService Stopped
Telephony Manual Own Process NT AUTHORITY\NetworkService Stopped
Remote Desktop Services Manual Share Process NT Authority\NetworkService Running
Windows Event Collector Manual Share Process NT AUTHORITY\NetworkService Stopped
Windows Remote Management (WS-Management) Auto Share Process NT AUTHORITY\NetworkService Running
Application Layer Gateway Service Manual Own Process NT AUTHORITY\LocalService Stopped
Application Identity Manual Share Process NT Authority\LocalService Stopped



Click to view the following information:

Display Name, Service Name, Error Control, Group, and Path





Click to view the following information:

Display Name, Dependencies



Chapter 3

4 Built-in Reports

4.1 About Built-in Reports

Built-in reports are a set of predefined reports that are based on some of the common tasks in Systems management reporting. Built-in reports are easy to use and speeds-up the report generation process.

Built-in reports encompass some of the significant standard resource reports, and added to that, additional reports, all of which could be generated across domains.

The built-in reports feature provides reports on the following resource categories:

- **Permissions Reports**
- **Shares and Resources**
- **Users and Groups**
- **Domains**

4.2 How to View Built-in Permissions Reports?

Permissions Reports

Permissions Reports includes reports that focus solely on reporting the access permissions assigned to users and groups on objects such as folders etcetera.

Click on 

button under ***Built-in Reports*** in button in the toolbar.

List of Permissions Reports

Report Name	Description
List of permissions for specific users and groups on folders	Reports the folder permissions assigned to specific users and/or groups on a selected set of folders.
List of permissions for folders	Reports the permissions associated with a selected set of folders.
List of permissions for specific users and groups on files	Reports the files permissions assigned to specific users and/or groups under a selected set of folders.
List of permissions for files	Reports the permissions associated with files under a selected set of folders

How to View Built-in Permissions Reports?

List of Permissions for Specific Users and Groups on Folders

This report allows you to view folder permissions for specific users and groups.

Click on 

button under Built-in Reports button in the toolbar.

The Built-in Reports window with the list of reports will be displayed as shown below:

Step 1: Report Selection

Select the report to be generated. Only one report can be generated at a time.


Built-in Reports - List of permissions for specific users and groups on folders
Step 1 of 3 : Select Report
Select a report from the available Built-in Reports.
Permissions
List of permissions for specific users and groups on folders
List of permissions for folders
List of permissions for specific users and groups on files
List of permissions for files
Description
This report lists the folder permissions assigned to a specific user/group account.
Back
Next
Close

Click **Next** to proceed to the *next* step.

Step 2: Select User/Group Accounts:

Select user and/or group accounts for which you would like to view the permissions for folders/files.



- Enter the name of User/Group in domain\account name format and click **Add to List** to add the name to selected accounts list
- Use **Select a Scan Profile (Users/Groups)** option to use the users and groups added in the profile.
- Use **Browse and Select** option to retrieve users and groups from servers or Scan Profile (Computers).



Use the **Find** option to search desired user/group accounts.

Click ***Next*** to Proceed.

Step 3: Select shared folders

Select one or more servers to retrieve available shares.




Built-in Reports - List of permissions for specific users and groups on folders
Step 3 of 3 : Select Shared Folder(s)
Enter the full path of a Share or Shared Folder. Click Add From to load the list of shares, Import to import a list of UNC folder paths from a text file. Select a folder in the list below and Click Edit Folder Options to modify the default properties for scanning each folder.
Share/Folder UNC Path:
Add
Scan Profile (Shares):
Sample Scans
Folder Path
Include sub-folders
Folder level
\\RD49\Address True All
\\RD49\ADMIN$ True All
\\RD49\C$ True All
\\RD49\D$ True All
\\RD49\E$ True All
\\RD49\ExchangeOAB True All
\\RD49\F$ True All
\\RD49\H$ True All
Add From
Import
Remove
Do not display folders that have the same permissions as the parent folder
Edit Folder Options
Include group membership information
Include SID
Back
Finish
Close

You may also type the UNC path of a folder that is not in the list, such as a folder that is not shared, and then click Add, to add it to the list. In addition, you may also import a list of UNC paths to shared and non-shared folders from a text file by using the Import button.

Folders that have identical permissions as the parent folder would show up with "Same as parent" in User Name and/or Security fields in the report. However, if you do not want folders with identical permissions as the parent folder reported, then select **Do not display folders that have same permissions as the parent folder** option. This option will not report folders with identical permissions as the parent folder.

NOTE: The "Do not display folders that have same permissions as the parent folder" option would be enabled by default.

ARKWE defaults to scanning all the sub-folders under a given shared folder. If you want to change the Include sub-folders and Folder level options click **Edit**

Folder Options



Click ***OK*** to *Proceed.*

Click ***Finish*** to generate the selected report.

After the data collection process is complete, the report would be generated in a report window as shown below:



How to view Built-in Permissions Reports?

List of Permissions for Folders

Click on 

button under Built-in Reports button in the toolbar.

The Built-in Reports window with the list of reports will be displayed as shown below:

Step 1: Report Selection

Select the report to be generated. Only one report can be generated at a time.


Built-in Reports - List of permissions for folders
Step 1 of 2 : Select Report
Select a report from the available Built-in Reports.
Permissions
List of permissions for specific users and groups on folders
List of permissions for folders
List of permissions for specific users and groups on files
List of permissions for files
Description
This report lists the permissions assigned to a specific folder.
Back
Next
Close

Click ***Next*** to the Proceed to the *Next* Step.

Step 2: Select shared folders:

Select one or more servers to retrieve available shares




Built-in Reports - List of permissions for folders
Step 2 of 2 : Select server(s) for Shared Folders-list
Enter the full path of a Share or Shared Folder. Click Add From to load the list of shares, Import to import a list of UNC folder paths from a text file. Select a folder in the list below and Click Edit Folder Options to modify the default properties for scanning each folder.
Share/Folder UNC Path:
Add
Scan Profile (Shares):
Sample Scans
Folder Path
Include sub-folders
Folder level
\\RD49\Address True All
\\RD49\ADMIN$ True All
\\RD49\C$ True All
\\RD49\D$ True All
\\RD49\E$ True All
\\RD49\ExchangeOAB True All
\\RD49\F$ True All
\\RD49\H$ True All
Add From
Import
Remove
Do not display folders that have the same permissions as the parent folder
Include group membership information
Include SID
Edit Folder Options
Back
Finish
Close

You may also type the UNC path of a folder that is not in the list, such as a folder that is not shared, and then click **Add**, to add it to the list. In addition, you may also import a

list of UNC paths to shared and non-shared folders from a text file by using the **Import** button.

Folders that have identical permissions as the parent folder would show up with "Same as parent" in User Name and/or Security fields in the report. However, if you do not want folders with identical permissions as the parent folder reported, then select **Do not display folders that have same permissions as the parent folder** option. This option will not report folders with identical permissions as the parent folder.

NOTE: The "Do not display folders that have same permissions as the parent folder" option would be enabled by default.

ARKWE defaults to scanning all the sub-folders under a given shared folder. If you want to change the Include sub-folders and Folder level options click **Edit Folder Options.**



Click ***OK*** to *Proceed.*

Click ***Finish*** to generate the selected report.

After the data collection process is complete, the report would be generated in a report window as shown below:



How to view Built-in Permissions Reports?

List of Permissions for Specific Users and Groups on Files

This report allows you to view file permissions for specific users and groups.

Click on 

button under Built-in Reports button in the toolbar.

The Built-in Reports window with the list of reports will be displayed as shown below:

Step 1: Report Selection

Select the report to be generated. Only one report can be generated at a time.


Built-in Reports - List of permissions for specific users and groups on files
Step 1 of 3 : Select Report
Select a report from the available Built-in Reports.
Permissions
List of permissions for specific users and groups on folders
List of permissions for folders
List of permissions for specific users and groups on files
List of permissions for files
Description
This report lists the file permissions assigned to a specific user/group account.
Back
Next
Close

Click ***Next*** to Proceed to the *Next* step.

Step 2: Select User/Group Accounts:

Select user and/or group accounts for which you would like to view the permissions for folders/files.



- Enter the name of User/Group in domain\account name format and click **Add to List** to add the name to selected accounts list.
- Use **Select a Scan Profile (Users/Groups)** option to use the users and groups added in the profile.
- Use **Browse and Select** option to retrieve users and groups from servers or Scan Profile (Computers).



Use the **Find** option to search desired user/group accounts. Click ***Next*** to Proceed.

Step 3: Select Shared Folders

Select one or more servers to retrieve available shares.




Built-in Reports - List of permissions for specific users and groups on files
Step 3 of 3 : Select Shared Folder(s)
Enter the full path of a Share or Shared Folder. Click Add From to load the list of shares, Import to import a list of UNC folder paths from a text file. Select a folder in the list below and Click Edit Folder Options to modify the default properties for scanning each folder.
Share/Folder UNC Path:
Add
Scan Profile (Shares):
Sample Scans
Folder Path
Include sub-folders
Folder level
\\RD49\Address True All
\\RD49\ADMIN$ True All
\\RD49\C$ True All
\\RD49\D$ True All
\\RD49\E$ True All
\\RD49\ExchangeOAB True All
\\RD49\F$ True All
\\RD49\H$ True All
Add From
Import
Remove
Do not display files that have the same permissions as the parent folder
Edit Folder Options
Include group membership information
Include SID
Back
Finish
Close

You may also type the UNC path of a folder that is not in the list, such as a folder that is not shared, and then click **Add**, to add it to the list. In addition, you may also import a list of UNC paths to shared and non-shared folders from a text file by using the Import button.

Folders that have identical permissions as the parent folder would show up with "Same as parent" in User Name and/or Security fields in the report. However, if you do not want folders with identical permissions as the parent folder reported, then select **Do not display folders that have same permissions as the parent folder** option. This option will not report folders with identical permissions as the parent folder.

NOTE: The "Do not display folders that have same permissions as the parent folder" option would be enabled by default.

ARKWE defaults to scanning all the sub-folders under a given shared folder. If you want to change the Include sub-folders and Folder level options click **Edit Folder Options.**



Click **OK** to Proceed.

Click **Finish** to generate the selected report.

After the data collection process is complete, the report would be generated in a report window as shown below:



How to View Built-in Permissions Reports?

List of Permissions for Files

This report allows you to view the associated permissions for specific files.

Click on 

button under Built-in Reports button in the toolbar.

The Built-in Reports window with the list of reports will be displayed as shown below:

Step 1: Report Selection

Select the report to be generated. Only one report can be generated at a time.


Built-in Reports - List of permissions for files
Step 1 of 2 : Select Report
Select a report from the available Built-in Reports.
Permissions
List of permissions for specific users and groups on folders
List of permissions for folders
List of permissions for specific users and groups on files
List of permissions for files
Description
This report lists the permissions assigned to files under a specific folder.
Back
Next
Close

Click ***Next*** to Proceed to the *Next* step.

Step 2: Select Shared Folders:

Select one or more servers to retrieve available shares




Built-in Reports - List of permissions for files
Step 2 of 2 : Select server(s) for Shared Folders-list
Enter the full path of a Share or Shared Folder. Click Add From to load the list of shares, Import to import a list of UNC folder paths from a text file. Select a folder in the list below and Click Edit Folder Options to modify the default properties for scanning each folder.
Share/Folder UNC Path:
Add
Scan Profile (Shares):
Sample Scans
Folder Path
Include sub-folders
Folder level
\\RD49\Address True All
\\RD49\ADMIN$ True All
\\RD49\C$ True All
\\RD49\D$ True All
\\RD49\E$ True All
\\RD49\ExchangeOAB True All
\\RD49\F$ True All
\\RD49\H$ True All
Add From
Import
Remove
Do not display files that have the same permissions as the parent folder
Edit Folder Options
Include group membership information
Include SID
Back
Finish
Close

You may also type the UNC path of a folder that is not in the list, such as a folder that is not shared, and then click **Add,** to add it to the list. In addition, you may also import a list of UNC paths to shared and non-shared folders from a text file by using the **Import** button.

Folders that have identical permissions as the parent folder would show up with "Same as parent" in User Name and/or Security fields in the report. However, if you do not want folders with identical permissions as the parent folder reported, then select **Do not display folders that have same permissions as the parent folder** option. This option will not report folders with identical permissions as the parent folder.

NOTE: The "Do not display folders that have same permissions as the parent folder" option would be enabled by default.

ARKWE defaults to scanning all the sub-folders under a given shared folder. If you want to change the Include sub-folders and Folder level options click **Edit Folder Options-folders and Folder level options click Edit Folder Options.**



Click ***OK*** to *Proceed.*

Click **Finish** to generate the selected report.

After the data collection process is complete, the report would be generated in a report window as shown below:



Folder/File Path	Folder/File Name	Folder/ Type	Owner	User Name	Security	Inherited	Apply To
\\RD45\test1	test1	Folder	BUILTIN\Administrat	Unknown Account	Allow - Special Acce	No	This folder, subfolders and files
				BUILTIN\Administrat	Allow - Full Control	No	This folder only
					Allow - Special Acce	No	This folder, subfolders and files
				PATHFINDER\admin	Allow - Full Control	No	This folder, subfolders and files
				PATHFINDER\crouch	Allow - Special Acce	No	This folder, subfolders and files
				Everyone	Allow - Special Acce	No	This folder, subfolders and files
				Unknown Account	Allow - Special Acce	No	This folder, subfolders and files
				PATHFINDER\Twst	Allow - Special Acce	No	This folder, subfolders and files
					Allow - Special Acce	No	This folder and subfolders
	Application Data Fol	Folder	BUILTIN\Administrat	Unknown Account	Allow - Special Acce	Yes	This folder, subfolders and files
				BUILTIN\Administrat	Allow - Special Acce	Yes	This folder, subfolders and files

4.3 How to View Built-in Reports for Shares and Resources?

Shares and Resources Reports

The Shares and Resources reports can be generated against domain(s) and specific server(s) as well.

Click on 

button under Built-in Reports in button in the toolbar.

The Built-in Reports window with the list of reports will be displayed as shown below:

Step 1: Report Selection

Select the report to be generated. Only one report can be generated at a time. Click Next to proceed to the next step.


Built-in Reports
Step 1 of 3 : Select Report
This window shows the list of Built-in reports available for the selected Built-in report category. Select any Report to proceed.
Shares and Resources
List of Shares
List of Shares with permissions
Back
Next
Close

Step 2: Select Domain (s) / Server(s)

Select the server(s)/Domain (s), for which the report needs to be generated.

The default option selected is All Domains, for all the reports.


Built-in Reports - List of Shares with permissions
Step 2 of 3 : Select Domain(s)/Server(s)
You can either generate the report across domains by selecting All Domains or for a specific domain/server by selecting the Select Domain/Server option. This report can also be generated specifically for a single server by selecting the Server option.
All Domains
Select Domain/Server
Add Domains
RD83
RESEARCHLAB
VOYAGER
Domain Controllers
RD40
Servers
RD41
RD43
Select Scan Profile:
--Select a Profile--
Back
Next
Close

Click Next to proceed to the next step.

Step 3: Select Report Criteria

To view the part of the report that is of more significance, change the report criteria settings. Only the data that matches the specified criteria will be displayed in the generated report.


Built-in Reports - List of Shares with permissions
Step 3 of 3 : Select Report Criteria
To view the part of the report that is of more significance, change the report criteria settings. Only the data that matches the specified criteria will be displayed in the generated report.
Share Type:
Folder Share
Admin Share
Back
Finish
Close

Click Finish to generate the selected report.

After the data collection process is complete, the report would be generated in a report window as shown below:



Domain/Server	Share Name	Path	User Name	Security	Maximum Uses	Comment
RD40	ADMIN$	C:\Windows		Admin Share	Unlimited	Remote Admin
	C$	C:\		Admin Share	Unlimited	Default share
	D$	D:\		Admin Share	Unlimited	Default share
	Folder	D:\Folder	BUILTIN\Administrators	Allow - Full Control	Unlimited	
		D:\Folder	Everyone	Allow - Full Control	Unlimited	
	latest setup	D:\latest setup	BUILTIN\Administrators	Allow - Full Control	Unlimited	Latest Setup Share
		D:\latest setup	Everyone	Allow - Full Control	Unlimited	Latest Setup Share
	Module	D:\Module	BUILTIN\Administrators	Allow - Full Control	Unlimited	
		D:\Module	Everyone	Allow - Full Control	Unlimited	
	NETLOGON	C:\Windows\SYSVOL\sysvol\Voyager.local\SCRIPTS	Everyone	Allow - Read	Unlimited	Logon server share
		C:\Windows\SYSVOL\sysvol\Voyager.local\SCRIPTS	BUILTIN\Administrators	Allow - Full Control	Unlimited	Logon server share
	NTFS Share	C:\NTFS Test Folder\NTFS Share	VOYAGER\adminuser3	Allow - Full Control	Unlimited	
	NTFS Test Folder	C:\NTFS Test Folder	Everyone	Allow - Read	Unlimited	
	Share	D:\Share	Everyone	Allow - Full Control	Unlimited	
		D:\Share	BUILTIN\Administrators	Allow - Full Control	Unlimited	
	share22	D:\share22	BUILTIN\Administrators	Allow - Full Control	Unlimited	
		D:\share22	Everyone	Allow - Full Control	Unlimited	
	SPListX Target	D:\SPListX Target	BUILTIN\Administrators	Allow - Full Control	Unlimited	
		D:\SPListX Target	Everyone	Allow - Full Control	Unlimited	

List of Reports:

Report Name	Description
List of Shares	Reports all the shares and their properties excluding the permission information.
List of Shares with Permissions	Reports all the shares and their properties including the permission information.

4.4 How to View Built-in Reports for Users and Groups?

Users and Groups Reports

The Users and Groups reports, contains reports that can be generated against domain(s) and specific sever(s) as well.

Click on 

button under Built-in Reports in button in the toolbar.

The Built-in Reports window with the list of reports will be displayed as shown below:

Step 1: Report Selection

Select the report to be generated. Only one report can be generated at a time. Click **Next** to proceed to the next step.


Built-in Reports - List of User accounts
Step 1 of 3 : Select Report
This report lists all Built-in and Custom User accounts in a machine.
Users and Groups
List of Users and Groups
List of User accounts
List of Local and Global groups
List of disabled user accounts
List of locked-out user accounts
Password settings of all user accounts (Password never expires etc.)
Members of Local Administrators group
Log on rights assigned for all accounts (Log on locally etc.)
Privileges assigned for all accounts
Group membership with nested groups
Back
Next
Close

Step 2: Select Domain (s) / Server(s)

Select the server(s)/Domain (s) or Select a Scan Profile, for which the report needs to be generated.

The default option selected is All Domains, for all the reports.


Built-in Reports - List of User accounts
Step 2 of 3 : Select Domain(s)/Server(s)
You can either generate the report across domains by selecting All Domains or for a specific domain/server by selecting the Select Domain/Server option. This report can also be generated specifically for a single server by selecting the Server option.
All Domains
Select Domain/Server
Add Domains
RESEARCHLAB
TREELAB
VSSLAB
Select Scan Profile:
--Select a Profile--
Back
Next
Close

Click **Next** to proceed to the next step.

Step 3: Select Report Criteria

To view the part of the report that is of more significance, change the report criteria settings. Only the data that matches the specified criteria will be displayed in the generated report.


Built-in Reports - List of User accounts
Step 3 of 3 : Select Report Criteria
To view the part of the report that is of more significance, change the report criteria settings. Only the data that matches the specified criteria will be displayed in the generated report.
User Type:
Built-in User
Custom User
Back
Finish
Close

Click **Finish** to generate the selected report.

After the data collection process is complete, the report would be generated in a report window as shown below:



List of Reports:

Report Name	Description
List of Users and Groups	Reports both the user and group accounts.
List of User accounts	Reports only the user accounts. This report lists both built-in and custom users.
List of Local and Global groups	Reports only the group accounts with member information. This report lists all Local groups for all the servers and also the Global groups if the server happens to be a PDC.
List of disabled user accounts	Reports only the user accounts, both built-in and custom, that have been disabled and/or otherwise.
List of locked-out user accounts	Reports only the user accounts, both built-in and custom, that have been locked out and/or otherwise.
Password settings of all user accounts (Password never expires etc.)	Reports password settings of the users' viz., Password never expires, User must change password at next logon, User cannot change password.
Members of Local Administrators group	Reports user and/or group members for the given group(s).
Log on rights assigned for all accounts (Log on locally etc.)	Reports user and/or group accounts having the logon rights viz., Log on locally, Log on as a service, Log on as a batch job.
Privileges assigned for all accounts	Reports the assigned privileges for both user and group accounts.
Group membership with nested groups	Reports all the members of a group along with their sub-group members.

4.5 How to View Built-in Reports for Domains?

Domains Reports

Domain Reports are generated across for the entire domain.

Click on 

button under Built-in Reports in button in the toolbar.

The Built-in Reports window with the list of reports will be displayed as shown below:

Step 1: Report Selection

Select the report to be generated. Only one report can be generated at a time. Click **Next** to proceed to the next step.


Built-in Reports - List of trusted and trusting domains
Step 1 of 3 : Select Report
This window shows the list of Built-in reports available for the selected Built-in report category. Select any Report to proceed.
Domains
List of trusted and trusting domains
List of machines with their OS and service pack
List of Windows Servers
List of Domain Controllers
List of Application Servers (IIS, Exchange Server, SQL Server etc.)
List of machines that run TCPIP services (FTP, telnet etc.)
List of machines that have auditing enabled (or disabled)
Back
Next
Close

Step 2: Select Domain (s) / Server(s)

Select the server(s)/Domain (s) or Select a Scan Profile, for which the report needs to be generated.

The default option selected is All Domains, for all the reports.


Built-in Reports - List of trusted and trusting domains
Step 2 of 3 : Select Domain(s)/Server(s)
You can either generate the report across domains by selecting All Domains or for a specific domain by selecting the Select Domain option.
All Domains
Select Domain
Add Domains
RESEARCHLAB
TREELAB
VSSLAB
Select Scan Profile:
--Select a Profile--
Back
Next
Close

Click **Next** to proceed to the next step.

Step 3: Select Report Criteria

To view the part of the report that is of more significance, change the report criteria settings. Only the data that matches the specified criteria will be displayed in the generated report.


Built-in Reports - List of trusted and trusting domains
Step 3 of 3 : Select Report Criteria
To view the part of the report that is of more significance, change the report criteria settings. Only the data that matches the specified criteria will be displayed in the generated report.
Trusted/Trusting Domains:
Trusted
Trusting
Back
Finish
Close

Click **Finish** to generate the selected report.

After the data collection process is complete, the report would be generated in a report window as shown below:



List of Reports:

Report Name	Description
List of trusted and trusting domains	Reports the trusted and/or trusting domains.
List of machines with their OS and service pack	Reports the configuration information of all the servers in the domain(s).
List of Windows Servers	Reports the OS installed in all the servers in the domain(s).
List of Domain Controllers	Reports the Primary and/or Backup Domain Controllers in the domain(s).
List of Application servers (IIS, Exchange Server, SQL Server etc.)	Reports servers running IIS and/or Exchange Server and/or SQL Server in the domain(s).
List of machines that run TCPIP services (FTP, telnet etc.)	Reports Servers running network services viz., TCP/IP, FTP, and Telnet in the domain.
List of machines that have auditing enabled (or disabled)	Reports the Auditing status of servers in the domain(s)...

Chapter 4

5 System Information

5.1 About System Info

This page covers the following topics:

- **Introduction**
- **Prerequisites and Initial Configuration**
- **System Info reports**

Introduction

The System Info feature provides significant hardware and software inventory-based reports that can be generated across domains. Further, all the System Info reports can also be scheduled for off-line generation using the Power Export tool.

Please be aware that the System Info feature uses WMI (Windows Management Instrumentation) to collect report data. Hence, all System Info reports require WMI to be installed and enabled on the source computer and target computers. For more information refer to "Prerequisites and Initial Configuration" section.

Prerequisites and Initial Configuration

The System Info feature uses WMI to collect report data. WMI uses DCOM protocol and is affected by Windows Firewall and DCOM security settings. In order to generate System Info reports both Windows Firewall and DCOM must be properly configured. Windows Firewall and DCOM, when not properly configured on your remote computers, can cause errors such as an "RPC Server Unavailable" error or an "Access is denied" error. Also, ensure that the current user context or specified user context, under which the application runs, is a local administrator on target computers.

In order to generate System Info reports ensure the following settings are set appropriately:

- Remote Administration setting is enabled on Windows Firewall. By default, Windows Firewall blocks all unsolicited incoming traffic except for Group Policy. This is a

common issue you might encounter while generating System Info reports. To resolve this issue, you need to enable the remote administration setting on the Firewall. For more information see Technical FAQ #19. For more information about configuring the Windows Firewall connections with a script, see http://www.microsoft.com/technet/community/columns/scripts/sg1104.mspx#EJAA

- WMI is installed and the Startup Type for WMI service is set to Automatic and the service is running under Local System Account.
- DCOM is enabled and ensure that security settings for DCOM allow remote connections
  1) Run the DCOM Configuration Utility (dcomcnfg.exe)
  2) In the **Component Services** dialog box, expand **Component Services**, expand **Computers,** and then right-click **My Computer** and click **Properties**
  3) In the **My Computer Properties** dialog box, click the **Default Properties** tab
  4) **Select Enable Distributed COM on this computer**
  5) The **Default Authentication Level** is set to **Connect** and the **Default Impersonation Level** is set to Identify in Windows XP and later operating systems. For Windows NT, however, the **Default Authentication Level** is set to **Connect** and **Default Impersonation Level is set to Impersonate**
  6) The default DCOM security settings for **Access Permissions** and **Launch and Activation Permissions** in the **COM Security** tab in the **My Computer Properties** dialog includes at least INTERACTIVE, SYSTEM and Administrators
- In Windows XP SP2 and later operating systems the SERVICE account is granted **Impersonate a client after authentication** right under **User Rights Assignment** under **Local Policies**
- The **Data Execution Prevention** in Windows XP SP2 and Windows 2003 SP1 is enabled for essential windows programs only

System Info Reports: The System Info feature provides reports on the following resource categories:

- **Network Configuration**
- **Operating System & Hot Fixes**
- **Printer Info**
- **Hardware Info**
- **Display Configuration**
- **Internet Explorer Configuration**
- **Current Status**
- **Environment Info**

5.2 How to View Network Configuration Reports?

Click on 

under System Info button to view Network Configuration information available under each tab as listed below.

NOTE: For information on restricting the domain scan for generating Network Configuration reports, please see How to scan specific servers in a domain?

Click 

tab to view the following information: **Network Adapter Name, IP Address, Subnet Mask, DHCP Enabled, Default Gateway, DHCP Server, DNS Servers, DNS Domain DHCP Lease Obtained, and DHCP Lease Expires.**



Click  tab to view the following information: ***Host Name, Account Name, and Last Logon to Computer.***

Click  tab to view the following information: ***Host Name, Adapter Name, Adapter Type, Adapter ID, Description, and Physical Address.***

Click Network Protocols tab to view the following information: ***Host Name, Protocol Name, Description, and Installed Date.***



5.3 How to View Operating System & Hot Fixes Reports?

Click on 

under System Info button to view OS and Hot Fixes information available under each tab as listed below.

NOTE: For information on restricting the domain scan for generating Operating System and Hot Fixes reports, please see How to scan specific servers in a domain?

Click 

tab to view the following information: ***Host Name, Operating System, Service Pack, Version, Product ID, Build Type, Total Virtual Memory (MB), Installed Date, Time Zone, and Page File Location(s).***



Click Hot Fixes tab to view the following information: ***Host Name, Hot Fix, Description, Installed By, Installed Date, Fix Comments, and Service Pack.***



5.4 How to View Printer Configuration Reports?

Click on 

under System Info button to view Printer Configuration information available under each tab as listed below.

NOTE: For information on restricting the domain scan for generating Printer Configuration reports, please see How to scan specific servers in a domain?

Click

tab to view the following information: ***Host Name, Printer Name, Description, Location, Share Name, Port Name, and Driver Name.***



5.5 How to View Hardware Configuration Reports?



Click on under System Info button to view Hardware Configuration information available under each tab as listed.

NOTE: For information on restricting the domain scan for generating Hardware Configuration reports, please see How to scan specific servers in a domain?

Click Summary tab to view the following information: ***Host Name, Number of Processor(s), System Model, System Manufacturer, System type, Total Physical Memory (MB), BIOS Version, Boot Device, Windows Directory, System Directory, System Locale, Processor(s), Network Adapter(s), IP Address, Disk(s), Disk Capacity (GB), and Number of Partitions in Disk.***



Click BIOS Info tab to view the following information: ***Host Name, BIOS Name, Version, and Release Date.***



Click Processors tab to view the following information**:** ***Host Name, Processor, Type, Description, Version, and Number of Processors.***



Click Physical Memory tab to view the following information: ***Host Name, Memory Identifier, Type, Capacity (MB), and Memory Bank.***



Click Disk Drives tab to view the following information**:** ***Host Name, Drive, Type, Capacity (GB), Space Used (GB), and Space Free (GB).***



5.6 How to View Display Configuration Reports?

Click on 

under System Info button to view Display configuration information available under each tab as listed below.

NOTE: For information on restricting the domain scan for generating Display configuration reports, please see How to scan specific servers in a domain?

Click

tab to view the following information**: *Host Name, Monitor Name, DPI Setting, Screen Refresh Rate, Screen Resolution, and Manufacturer.***



Click Video Adapter Info tab to view the following information**: *Host Name, Adapter Name, Video Mode, Color Quality, Memory Size (MB), Driver Date, Driver Version, and DAC Type.***



5.7 How to View Internet Explorer Configuration Reports?

Click on 

under System Info button to view Internet Explorer configuration information available under each tab as listed below:

NOTE: For information on restricting the domain scan for generating Internet Explorer configuration reports, please see How to scan specific servers in a domain?

Click

tab to view the following information**: *Host Name, Version, Cipher Strength, Product ID, Build Number, Content Advisor, Location, and Language.***



5.8 How to View Current Status Reports?

Click on 

under System Info button to view Current Status information available under each tab as listed below:

NOTE: For information on restricting the domain scan for generating Current Status reports, please see How to scan specific servers in a domain?

Click

tab to view the following information**: *Host Name, Current Local Time, Last Boot up Time, System Uptime, Percentage of Memory Used, CPU Busy (in percentage), Currently Logged on User, User Logged on Since, Time Elapsed since Logon, and Status Recorded as on.***

NOTE: The **Current Local Time** field displays the local time of the target computer (reported in Host Name field). **The Status Recorded as on** field displays the time at which report data was collected for the respective target computer.



5.9 How to View Environment Info Reports?



Click on under System Info button to view Environment Information available under each tab as listed below.

NOTE: For information on restricting the domain scan for generating Environment Info reports, please see How to scan specific servers in a domain?

Click Summary tab to view the following information**: *Host Name, OS, System Drive, System Root, Temp (System), Tmp (System), Path extension, Path, Default User Domain User DNS Domain, Common Program Files, Program Files, All Users APP Data, All User Profile, and Command Prompt Location.***



Chapter 5

6 Additional Features

6.1 How to customize fields?

Click on 

for customizing the information.



Click

for selecting all the check boxes.

Click 

for clearing all the check boxes.

Click

button for confirming the changes.

Click 

button for cancelling the operation.

6.2 How to Apply Filters?

Click 

for setting filter options

The ARKWE Filter window will be displayed. .



To set a filter condition, follow these steps.

1) **Click** (Clear All) button and clear the filter.
2) **Choose** a field name, an operator and a possible value from the respective dropdown options.
3) **Click**

4) **The Add to Filter will change to AND to Filter. The OR to Filter button will be enabled.** The selected condition will be set as a filter and displayed (as shown below).



5) **Click OK** to apply the filter.

NOTE:

- **Use the** AND to Filter **,** 'OR' to Filter **and** ( ) **to build enhanced filter condition as shown below:**
- **(Field A = Value 1 AND Field B = Value 2) OR (Field C = Value 3 AND Field D = Value 4)**
- **Use** **to remove the parenthesis**
- **Use** **to delete a selected condition.**

The status bar's FILTERED indicator is used to indicate whether the current data is filtered or not.

For a normal view, the status bar will appear as

For a filtered view, the status bar will appear as Filtered

6.3 How to Refresh Data?

Refresh the current report data to view the latest information from the Domain Controller.

Click on 

button in the toolbar available in the report window or press F5 to refresh report data. Alternatively, you can right-click on the grid, in the right pane of the report window, and then select 'Refresh Data' from the context menu. The existing data will be cleared and latest data will be loaded in the report window.

6.4 How to Export Data?

The **Export** feature helps the user to export report data generated by ARKWE to a file using various formats namely HTML/CSV/XLSX/SQL.

Click 

for exporting the information in the desired format or select Export option under Tools menu to export report data to a file in the desired format.



Specify a file name to export report data to or accept the default file name. Specify the export path and select a desired file format. The path refers to the destination location where the output file generated should be stored. It can be given using the Browse button. To avoid overwrite existing files, if any, in the specified export path, By default, the report will be exported to a time-stamped sub-folder, in the format 'YYYY-MM-DD HH.MM.SS', under the specified export path.

In XLSX file format, the information is stored as sheets in Excel file. For each report, a XLSX file will be generated. The name of the XLSX file will be the name of the report and is stored in the specified destination path if "Export to time-stamped folder" option is cleared. The XLSX file will be stored under a sub-folder, of the form YYYY-MM-DD HH.MM.SS, under the specified export path, if "Export to time-stamped folder" option is set.

In CSV file format, the information is stored as comma separated values. For each report, a CSV file will be generated. The name of the CSV file will be the name of the report and is stored in the specified destination path if "Export to time-stamped folder" option is cleared or under a sub-folder, of the form YYYY-MM-DD HH.MM.SS, under the specified export path if "Export to time-stamped folder" option is set.

In SQL table format, the information is stored as SQL tables in the application database in the specified SQL server based on the selected SQL database option. For each report, a separate table will be created. The name of the table will be the name of the report.

In HTML file format, the information is stored as an html file. For each report, a HTML file will be generated. The name of the HTML file will be the name of the report and is stored in the specified destination path if "Export to time-stamped folder" option is cleared or under a sub-folder, of the form YYYY-MM-DD HH.MM.SS, under the specified export path if "Export to time-stamped folder" option is set.

6.5 How to E-mail Data?

ARKWE provides the option to e-mail the reports generated.

Click

button in the toolbar to e-mail the report to e-mail recipients. E-mail dialog will be displayed as shown below:



For e-mailing reports, ARKWE requires SMTP Server, From E-mail Address, To E-mail Addresses (recipients separated by semicolon) and the report attachment format.

Specify SMTP server name, from Address, "To" address, mail subject, mail content, attachment format and option to compress the attachment.

Click

button to send the report by e-mail to the selected recipients.

Check names

ARKWE provides check name feature to check the existence of corresponding mail-enabled recipient object in Active Directory. To check name, **click**

button. If the entered name matches with a mail object in the Active directory / its trusted domain, name entered in From Address textbox will be replaced by the corresponding active directory recipient object. If there is more than one match, a dialog which contains matching Active Directory recipients will appear as shown below. You can select one or more recipient and click **OK.**



- To get more information about the listed recipients under **Change to**, select the name, and then **click**



If there is no match for the name entered by the user in Active Directory, a dialog will appear as shown below:



Select Delete option in the above dialog to remove the recipient name from to address text box. Click Cancel button to close this dialog and the unresolved recipient(s) will appear in red color.

Address Book

ARKWE provides Address Book feature to search for any mail enabled recipient object (say, person, distribution list, contact, public folder) you want to send a message to. **Click** 

button and then use the **Find Names** dialog box to search for the recipient object you want to send a message to. (Note that you can't use the **Find Names** dialog box to search for distribution lists in your Contacts folder.) Select the object's name in the list and then click **Add recipient to...To.**



- To get more information about one of the names in the list, such as department or phone number, select the name, and then **click**

6.6 How to Find Data in a Report?

You can use the find feature in ARKWE to search for specific data in a report.

To search for data in a report, just type the characters or words you want to find in the find edit box available in the report window and click on 

. .

1) ARKWE performs a case insensitive search of the specified search criteria in the report.

2) The search criteria should not be enclosed within quotation marks.

3) You can use the "*" wildcard character in the search criteria. The "*" wildcard character act as a place holder for zero or more characters. However, note that you cannot use the "?" wildcard character in the search criteria.

For instance, if you want to search for 'Domain' in a report, Type Domain, without quotations, in the edit box, and then clicks on Find Button.

By default, ARKWE adds an asterisk as a suffix to the specified search criteria, if no wildcard character is present in it. In this case, ARKWE finds a match in the report for all fields that have the text Domain followed by zero or more characters, that is, Domain, Domain Controllers, Domain Admins, etc.

For all the matches found, ARKWE highlights the corresponding columns in the grid, and scrolls the grid automatically to the first occurrence.

4) ARKWE finds additional occurrences of the specified search criteria instantaneously. To locate other occurrences of the same search criteria in a report you need to scroll the report grid downwards.


Domains - Shares (PATHFINDER)
Refresh
Print/Preview
Export
Filter
Customize
E-mail
Find
everyone
Enterprise - DOMAINS
ADVENTURE
DISCOVERY
PATHFINDER
VSSPRO
VYAPINLAB
Shares
Host Name
Share Name
Path
User Name
Security
Maximum Uses
RD45
ADChangeTracker$
Everyone
Allow - Full Control
Unlimited
Address
Allow - Read
BUILTIN\Administ...
PATHFINDER\RD4...
ADMIN$
C:\WINDOWS
Admin Share
Bharath Source Cod
PATHFINDER\AD...
Bulk export for patcl
C$
C:\
F$
F:\
G
G:\
NETLOGON
BUILTIN\Administ...
PATHFINDER\Do...
RD45.LOG

6.7 How to Scan Specific Servers in a Domain?

You can have the System Info reports and summary information of a domain (namely Summary, Shares and Applications) generated either for an entire domain or for selected servers in the domain, using the 'Scan option for ...' dialog.

NOTE: This dialog appears, if either it is the first time the report is run against the domain or when you refresh the report.



ARKWE defaults to scanning the entire domain, with the provision to enumerate Domain Controllers, Servers, Workstations only. To scan only selected servers, you can either select the computers by using Scan Selected Server(s) in Domain option or by selecting Select a Scan Profile option.

By using the **Scan Selected Server(s) in Domain** option you can specify a computer list by manually typing in the computer name and adding it to the list, or by selecting computers from the network using the **Add From** button as shown below:



You may also apply a scan profile to the report to restrict the list of computers for which you want the report to be generated.



A Scan Profile essentially contains a list of computers that ARKWE can read and generate the report only for computers in the selected profile.

Click button to create a new Scan Profile. **Click** button to edit an existing Scan Profile.

However, please be aware, that the report will be generated only for computers, in the applied profile, belonging to the currently selected domain. This restriction does not apply if the report is being generated off-line using **Power Export tool.**

Click **OK** in the "Scan Option for..." dialog to generate the report.

If ARKWE could not find any computers belonging to the currently selected domain in the applied Scan Profile, you may see the following message show up on screen:



NOTE: Clicking **Cancel** in "Scan option for..." dialog will display previously collected report data (if any) for the domain.

Chapter 6

7 Power Export

7.1 About Power Export

ARKWE provides a powerful offline report generation tool called Power Export. Power Export allows the user to select multiple reports to be run for several domains and servers across the enterprise at scheduled intervals. The Power Export tool has the ability to export the reports in different file formats.

Please note the following while using the Power Export Wizard:

a) Scheduled reports will be created as a "task" in Windows Task Scheduler.

b) The scheduled job will generate and export the reports in different file formats (HTML MDB, CSV, PDF, XLSX and TIFF) to the desired folder path/printer.

c) By default, for each task, a sub-folder with the task name will be created under the specified export path. All selected Reports will be exported to a time-stamped sub-folder, in the format "yyyy-mm-dd hh.mm.ss", under the task name folder. Therefore, the full folder path for all the exported reports refers to the following directory: <Export path><Task name><Time stamp>.

d) A separate file will be created for each report in the desired file format. For example, in the HTML file format, each report will be created as an .html file.

NOTE:

ARKWE Power Export Wizard will help you create and store the settings for a task, which you may view or modify later using the Scheduled Tasks Manager. The task will be created with the settings (Schedule Type and Run As parameter) provided using the Power Export Wizard. A valid password must be specified for the Run As parameter of the task.

You can schedule the two types of reports (Standard report and Built-in report) available in ARKWE.

7.2 Task Manager-Scheduled Tasks Manager

The Scheduled Tasks Manager allows you to perform the following operations:

- View summary information for the tasks created
- View exported files of the task
- Edit an existing task
- Delete a task

View Summary Information of a Task

The pane on the left hand side in the Scheduled Tasks Manager window lists the tasks maintained in ARKWE. To view summary information of a task, select the desired task on the left pane. The summary information of the selected task will be displayed in the right pane as shown below:



The task summary includes information about the task information, reports selected, export settings.

To view the selected servers/domains for a report in the task, click on the hyperlink in the **Servers/Domains** column in the right pane. The **Selected Servers/Domains** window will be displayed as shown below:



View Exported Files

To view the reports generated and exported by the task, perform either one of the following steps:

- Select **Scheduled Tasks** node on the left pane, and then click on the hyperlink in the **Exported Files column** in the right pane for the desired task.

OR

- Select the desired task on the left pane, and then click on the hyperlink next to **Exported Files.**

Edit Task

1) Select a task from the Scheduled Tasks Manager Window and Click **Edit Task**.
2) Perform the steps as in Schedule Standard Report or Schedule Built-in Report based on the scheduled report type. While proceeding through the wizard you may change the settings, add a new report, delete a report, edit a report, change the export path etc.,
3) The new settings will be used when the task runs the next time.

Delete Task

To delete a task from the Power Reports Task Manager Window, select the task and Click Delete Task. The deleted task will be removed permanently from the Windows Task Scheduler.

7.3 Schedule Standard Reports

Select 

option under Power Export. This will bring up the Power Export Wizard.

Step 1: Report Selection



1) **Select** the report(s) using the checkboxes to the left of the reports. You may select any number of reports to run in a single task.
2) There are two categories of reports - Domain Reports and Server Reports.
3) Reports falling under 'Domain Reports' default to scanning and collecting data for the entire domain. However, you can also restrict the domain scope and scan and collect data only for a specific set of servers and have the domain reports generated (viz., Summary, Shares, and Applications).

4) Reports falling under 'Server Reports' scan each server and collect data specific to each server. They are further classified by the category they report on (viz. Users, Policies, and Events etc.).

5) **Click Next** to proceed to the next step. You may Click **Back** button anytime to come back to a previous step.

Step 2: Domain Selection for Domain Reports

NOTE: This step is applicable only if a Domain Report is selected in step 1.


Power Export - Standard Reports
Step 2 of 6 : Domain Selection
For each of the following reports, select the list of domains for which you would like to generate the report. Double-click on a report or click Add Domains. The report for each of the selected domains will be exported as a separate file.
Domains-Summary
Domains-Trust
Domains-Shares
Domains-Applications
NetworkConfigurations-IP Configuration
NetworkConfigurations-Login Profiles
NetworkConfigurations-Network Adapters
NetworkConfigurations-Network Protocols
OSInfos-Operating System Configuration
OSInfos-Hot Fixes
PrinterInfos-Printers
HardwareInfos-Summary
HardwareInfos-BIOS Info
HardwareInfos-Processors
Domain Name
No Domain Selected
Add Domains...
<Back
Next>
Close

1) Click **Add Domains** button to select the domains for which you wish to run the domain reports selected in Step 1. This will display a window where you can select the domains you want to add.


Select Domain(s)/Server(s)
Select one or more domains. Click on the Apply To button in order to apply the same list of domains for all the selected Reports.To generate the report for all servers in a domain, select the domain, or select a set of servers to restrict the domain scan. Or you may select a Scan Profile.
Select Domain/Server
RESEARCHLAB
TREELAB
VSSLAB
Select Scan Profile:
--Select a Profile--
Apply to Reports...
OK
Cancel

2) You can restrict the domain scope and scan and collect data only for a specific set of computers by either selecting specific computers under a domain or by selecting a Scan Profile.

3) Click **OK** to apply the selected domains or a Scan Profile to the current report or click **Apply to Reports** to apply the selection to the rest of the selected domain reports. The selected domains will be added to the wizard as shown below:


Power Export - Standard Reports
Step 2 of 6 : Domain Selection
For each of the following reports, select the list of domains for which you would like to generate the report. Double-click on a report or click Add Domains. The report for each of the selected domains will be exported as a separate file.
Domains-Summary
Domains-Trust
Domains-Shares
Domains-Applications
NetworkConfigurations-IP Configuration
NetworkConfigurations-Login Profiles
NetworkConfigurations-Network Adapters
NetworkConfigurations-Network Protocols
OSInfos-Operating System Configuration
OSInfos-Hot Fixes
PrinterInfos-Printers
HardwareInfos-Summary
HardwareInfos-BIOS Info
HardwareInfos-Processors
Domain Name
TREELAB [Full Scan]
Add Domains...
<Back
Next>
Close

4) Click **Next** to proceed to the next Step.

Step 3: Server Selection for Server Reports

NOTE: This step is applicable only if a Server Report is selected in step 1.


Power Export - Standard Reports
Step 3 of 6 : Server Selection
For each of the following reports, select the list of servers for which you would like to generate the report. Double-click on a report or click Add Servers. The report for each of the selected servers will be exported as a separate file.
Users and Groups-General
Users and Groups-Status
Server Name
No Server Selected
Add Servers...
<Back
Next>
Close

1) Click **Add Servers** button to select the servers for which you wish to run the server reports selected in Step 1. This will display a window where you can select the servers you want to add. Selecting a domain will add all the servers in that domain to the report.



2) You can restrict the domain scope and scan and collect data only for a specific set of computers by either selecting specific computers under a domain or by selecting a Scan Profile.

3) Click **OK** to apply the selected servers or a Scan Profile to the current report or click **Apply to Reports** to apply the selection to the rest of the selected server reports. The selected servers will be added to the wizard as shown below:


Power Export - Standard Reports
Step 3 of 6 : Server Selection
For each of the following reports, select the list of servers for which you would like to generate the report. Double-click on a report or click Add Servers. The report for each of the selected servers will be exported as a separate file.
Users and Groups-General
Users and Groups-Status
Server Name
TREELAB\RD50
TREELAB\RD73
VSSLAB\RD20
VSSLAB\RD21
VSSLAB\RD22
VSSLAB\RD24
VSSLAB\RD25
VSSLAB\RD26
VSSLAB\RD23
VSSLAB\RD05
VSSLAB\VMSRV02
Add Servers...
<Back
Next>
Close

4) Click **Next** to proceed to the Next step.

Step 4: Delivery Options


Power Export - Standard Reports
Step 4 of 6 : Delivery Options
Select the report delivery options. You can Export and E-mail the reports using the options below. In case of export option, for each task, a sub-folder with the task name will be created under the specified export path. All selected reports will be exported to a time-stamped folder in the format "yyyy-mm-dd hh.mm.ss" under the task name folder.
Export Type:
HTML
Export
Export Path :
C:\Users\Public\Documents\ARKWE 8.x\Export
...
E-mail
To Address:
Additional E-mail Settings...
Compress the attachment
Note: This evaluation version exports / e-mails only the first 10 records.
<Back
Next>
Close

1) Change the Export or E-mail settings as necessary.

2) Use Browse button to change the export path.

- Click **Additional E-mail Settings** button to specify optional e-mail settings as shown below:



Step 5: Schedule Settings



1) Enter a unique name for the task.
2) Change the Run as parameter, if necessary and set the password for the specified user.
3) Change the task schedule settings as required.
4) Click **Next** to proceed to the next and final step.

Step 6: Summary



1) This step displays the summary information of the task.
2) Click **Finish** to save the task details.
3) The task will be added to Windows Schedule Tasks and will be displayed in the Scheduled Tasks Manager Window as shown below:


Scheduled Tasks
Scheduled Tasks
TestEvents
Standard Report
Task Name: Standard Reports Task
Run As: PATHFINDER\adminuser
Report Type: Standard Report
Exported Files: Click here to view
Schedule: At 5:00 PM every day, starting 3/21/2013
Report Name
Servers/Domains
Export As
Export Folder (Export Path\Task Name)
ComputerStatusInfos-Summary
Click here to view
HTML
C:\Users\Public\Documents\ARKWE 8.x\Export\Standard Reports Task
DisplayConfigurations-Monitor Info
Click here to view
HTML
C:\Users\Public\Documents\ARKWE 8.x\Export\Standard Reports Task
DisplayConfigurations-Video Adapter Info
Click here to view
HTML
C:\Users\Public\Documents\ARKWE 8.x\Export\Standard Reports Task
Domains-Applications
Click here to view
HTML
C:\Users\Public\Documents\ARKWE 8.x\Export\Standard Reports Task
Domains-Shares
Click here to view
HTML
C:\Users\Public\Documents\ARKWE 8.x\Export\Standard Reports Task
Domains-Summary
Click here to view
HTML
C:\Users\Public\Documents\ARKWE 8.x\Export\Standard Reports Task
Domains-Trust
Click here to view
HTML
C:\Users\Public\Documents\ARKWE 8.x\Export\Standard Reports Task
EnvironmentInfos-Summary
Click here to view
HTML
C:\Users\Public\Documents\ARKWE 8.x\Export\Standard Reports Task
Edit Task...
Delete Task
Close

7.4 Schedule Built-in Reports

The built-in reports have been categorized to the following:

- **Permissions Reports**
- **Shares and Resources reports**
- **Users and Groups reports**
- **Domains reports**

Schedule Permissions Built-in Reports

Permissions Reports

Permissions Reports includes reports that focus solely on reporting the access permissions assigned to users and groups on objects such as folders etcetera.

- **List of permissions for specific users and groups on folders**
- **List of permissions for folders**
- **List of permissions for specific users and groups on files**
- **List of permissions for files**

Schedule Permissions Built-in Reports

List of Permissions for Specific Users and Groups on Folders

This report allows you to view folder permissions for specific users and groups.

Select 

option under Power Export. This will bring up the Power Export Wizard.

Step 1: Report Selection


Power Export - Built-in Reports
Step 1 of 6 : Report Selection
Select the desired report to proceed. Only one report can be selected in this category.
List of permissions for specific users and groups on folders
List of permissions for folders
List of permissions for specific users and groups on files
List of permissions for files
<Back
Next>
Close

1) Select **"Permissions Reports"** from the select report category drop-down list.

2) Select the desired report. Only one report may be selected to run in a single task.

3) Click **Next** to proceed to the next step. You may Click **Back** button anytime to come back to a previous step.

Step 2: User and/or Group Selection


Power Export - Built-in Reports
Step 2 of 6 : User/Group Selection
Select a server or a Scan Profile (Computers) or a Scan Profile (Users/Groups) to retrieve available users and groups from.
Report Name: List of permissions for specific users and groups on folders
Enter account name :
Add to list
Accounts from domain\server:
Browse and Select
Accounts from Scan Profiles (Users/Groups):
--Select a Profile--
Selected Accounts
Account Name
Account Type
Remove
Reset
<Back
Next>
Close



- Use **Select a Scan Profile (Users/Groups)** option to use the users and groups added in the profile. For more information on Scan Profiles, click About Scan Profiles (Users/Groups).

1) Select the user or group, for which you wish to run the permissions report.

2) The selected users will be added to the wizard as shown above:

3) Click ***Next*** to proceed to the Next step.

Step 3: Shared Folder Selection


Power Export - Built-in Reports
Step 3 of 6 : Shared Folder Selection
Enter the full path of a Share or Shared Folder. Click Add From to load the list of shares, Import to import a list of UNC folder paths from a text file. Select a folder in the list below and Click Edit Folder Options to modify the default properties for scanning each folder.
Report
List of permissions for specific users and groups on folders
UNC Path:
Add
Scan Profile (Shares):
<No Profile found.>
Folder Path
Include sub-fold...
Folder level
\\RD50\ADMIN$ True All
\\RD50\ARKWE True All
\\RD50\C$ True All
\\RD50\E$ True All
\\RD50\new True All
Add From...
Import
Remove
Do not display folders that have the same permissions as the parent folder
Edit Folder Options...
Include group membership information
Include SID
Validate for Errors
Include Error Details
Generate report ignoring any errors found
Generate report only if no errors were found. Send error report through e-mail
E-mail Settings
<Back
Next>
Close

1) Select the desired folder(s) for which you wish to run the permissions report.

2) You may also click **Import** button to import a list of UNC folder paths from a text file.

3) Folders that have identical permissions as the parent folder would show up with "Same as parent" in User Name and/or Security fields in the report. However, if you do not want folders with identical permissions as the parent folder reported, then select **Do not display folders that have same permissions as the parent folder** option. This option will not report folders with identical permissions as the parent folder.

4) ARKWE defaults to scanning all the sub-folders for a given folder. If you want to modify the Include sub-folders and sub-folder level options click **Edit Folder Options** button. That will show up a window as shown below:



5) Modify the folder options as required and click **OK.**

6) Select the **Validate for Errors** option for validating the folders / files based on the folder traversal option selected, before proceeding to report generation.

- **Generate report ignoring any errors found –** This option will validate the folders/ files path(s) and generate the report even if errors are encountered during the validation option.
- **Generate report only if no error were found. Send error report through e-mail** – This option will validate the folders/ files path(s) and skip the report generation if errors were encountered during the validation option. It will then email the error(s) encountered during the validation process to users

7) You may select **Include Error Details** option for including the error information of folders / files into report data.

8) Click **Next** to proceed to the Next step.

Step 4: Delivery Options


Power Export - Standard Reports
Step 4 of 6 : Delivery Options
Select the report delivery options. You can Export and E-mail the reports using the options below. In case of export option, for each task, a sub-folder with the task name will be created under the specified export path. All selected reports will be exported to a time-stamped folder in the format "yyyy-mm-dd hh.mm.ss" under the task name folder.
Export Type:
HTML
Export
Export Path :
C:\Users\Public\Documents\ARKWE 8.x\Export
...
E-mail
To Address:
Additional E-mail Settings...
Compress the attachment
Note: This evaluation version exports / e-mails only the first 10 records.
<Back
Next>
Close

1) Change the Export or E-mail settings as necessary.
2) Use Browse button to change the export path.

Click **Additional E-mail** Settings button to specify optional e-mail settings as shown below:



Step 5: Schedule Settings



1) Enter a unique name for the task.

2) Change the Run as parameter, if necessary and set the password for the specified user.

3) Change the task schedule settings as required.

4) Click ***Next*** to proceed to the next and final step.

Step 6: Summary



1) This step displays the summary information of the task.

2) Click **Finish** to save the task details.

3) The task will be added to Windows Schedule Tasks.

Schedule Permissions Built-in Reports

List of Permissions for Folders

This report, allows you to view the associated folder permissions for a set of folders.

Select 

option under Power Export. This will bring up the Power Export Wizard.

Step 1: Report Selection


Power Export - Built-in Reports
Step 1 of 5 : Report Selection
Select the desired report to proceed. Only one report can be selected in this category.
List of permissions for specific users and groups on folders
List of permissions for folders
List of permissions for specific users and groups on files
List of permissions for files
<Back
Next>
Close

1) Select **"Permissions Reports"** from the select report category drop-down list.
2) Select the desired report. Only one report may be selected to run in a single task.
3) Click **Next** to proceed to the next step. You may Click **Back** button anytime to come back to a previous step.

Step 2: Shared Folder Selection


Power Export - Built-in Reports
Step 2 of 5 : Shared Folder Selection
Enter the full path of a Share or Shared Folder. Click Add From to load the list of shares, Import to import a list of UNC folder paths from a text file. Select a folder in the list below and Click Edit Folder Options to modify the default properties for scanning each folder.
Report List of permissions for folders
UNC Path:
Add
Scan Profile (Shares):
<No Profile found.>
Folder Path
Include sub-fold...
Folder level
\\RD50\ADMIN$ True All
\\RD50\ARKWE True All
\\RD50\C$ True All
\\RD50\E$ True All
\\RD50\new True All
Add From...
Import
Remove
Do not display folders that have the same permissions as the parent folder
Edit Folder Options...
Include group membership information
Include SID
Validate for Errors
Include Error Details
Generate report ignoring any errors found
Generate report only if no errors were found. Send error report through e-mail
E-mail Settings
<Back
Next>
Close

1) Select the desired folder(s) for which you wish to run the permissions report.

2) You may also click **Import** button to import a list of UNC folder paths from a text file.

3) Folders that have identical permissions as the parent folder would show up with "Same as parent" in User Name and/or Security fields in the report. However, if you do not want folders with identical permissions as the parent folder reported, then select **Do not display folders that have same permissions as the parent folder** option. This option will not report folders with identical permissions as the parent folder.

4) ARKWE defaults to scanning all the sub-folders for a given folder. If you want to modify the Include sub-folders and sub-folder level options click **Edit Folder Options** button. That will show up a window as shown below:



5) Modify the folder options as required and click **OK.**

6) Select the **Validate for Errors** option for validating the folders / files based on the folder traversal option selected, before proceeding to report generation.

- **Generate report ignoring any errors found –** This option will validate the folders/ files path(s) and generate the report even if errors are encountered during the validation option.
- **Generate report only if no error were found. Send error report through e-mail –** This option will validate the folders/ files path(s) and skip the report generation if errors were encountered during the validation option. It will then email the error(s) encountered during the validation process to users.

7) You may select **Include Error Details** option for including the error information of folders / files into report data.

8) Click ***Next*** to proceed to t to proceed to the *Next* step.

Step 3: Delivery Options


Power Export - Standard Reports
Step 4 of 6 : Delivery Options
Select the report delivery options. You can Export and E-mail the reports using the options below. In case of export option, for each task, a sub-folder with the task name will be created under the specified export path. All selected reports will be exported to a time-stamped folder in the format "yyyy-mm-dd hh.mm.ss" under the task name folder.
Export Type:
HTML
Export
Export Path :
C:\Users\Public\Documents\ARKWE 8.x\Export
...
E-mail
To Address:
Additional E-mail Settings...
Compress the attachment
Note: This evaluation version exports / e-mails only the first 10 records.
<Back
Next>
Close

1) Change the Export or E-mail settings as necessary.

2) Use Browse button to change the export path.

Click **Additional E-mail Settings** button to specify optional e-mail settings as shown below:



Step 4: Schedule Settings



1) Enter a unique name for the task.
2) Change the Run as parameter, if necessary and set the password for the specified user.
3) Change the task schedule settings as required.
4) Click **Next** to proceed to the next and final step.

Step 5: Summary



1) This step displays the summary information of the task.
2) Click **Finish** to save the task details.
3) The task will be added to Windows Schedule Tasks.

Schedule Permissions Built-in Reports

List of Permissions for Specific Users and Groups on Files

This report allows you to view file permissions for specific users and groups.

Select 

option under *Power Export.*

This will bring up the *Power Export Wizard.*

Step 1: Report Selection


Power Export - Built-in Reports
Step 1 of 6 : Report Selection
Select the desired report to proceed. Only one report can be selected in this category.
List of permissions for specific users and groups on folders
List of permissions for folders
List of permissions for specific users and groups on files
List of permissions for files
<Back
Next>
Close

1) Select **"Permissions Reports"** from the select report category drop-down list.
2) Select the desired report. Only one report may be selected to run in a single task.
3) Click ***Next*** to proceed to the next step. You may Click ***Back*** button anytime to come back to a previous step.

Step 2: User and/or Group Selection


Power Export - Built-in Reports
Step 2 of 6 : User/Group Selection
Select a server or a Scan Profile (Computers) or a Scan Profile (Users/Groups) to retrieve available users and groups from.
Report Name: List of permissions for specific users and groups on files
Enter account name :
Add to list
Accounts from domain\server:
Browse and Select
Accounts from Scan Profiles (Users/Groups):
--Select a Profile--
Selected Accounts
Account Name
Account Type
Remove
Reset
<Back
Next>
Close



- Use **Select a Scan Profile (Users/Groups)** option to use the users and groups added in the profile. For more information on Scan Profiles, Please refer, "About Scan Profiles (Users/Groups)."

1) Select the user or group, for which you wish to run the permissions report.

2) The selected users will be added to the wizard as shown above:

3) Click **Next** to proceed to the *Next* step.

Step 3: Shared Folder Selection


Power Export - Built-in Reports
Step 3 of 6 : Shared Folder Selection
Enter the full path of a Share or Shared Folder. Click Add From to load the list of shares, Import to import a list of UNC folder paths from a text file. Select a folder in the list below and Click Edit Folder Options to modify the default properties for scanning each folder.
Report List of permissions for specific users and groups on folders
UNC Path:
Add
Scan Profile (Shares):
<No Profile found.>
Folder Path
Include sub-fold...
Folder level
\\RD50\ADMIN$ True All
\\RD50\ARKWE True All
\\RD50\C$ True All
\\RD50\E$ True All
\\RD50\new True All
Add From...
Import
Remove
Do not display folders that have the same permissions as the parent folder
Edit Folder Options...
Include group membership information
Include SID
Validate for Errors
Include Error Details
Generate report ignoring any errors found
Generate report only if no errors were found. Send error report through e-mail
E-mail Settings
<Back
Next>
Close

1) Select the desired folder(s) for which you wish to run the permissions report.

2) You may also click **Import** button to import a list of UNC folder paths from a text file.

3) Files that have identical permissions as the parent folder would show up with "Same as parent" in User Name and/or Security fields in the report. However, if you do not want files with identical permissions as the parent folder reported, then select **Do not display files that have same permissions as the parent folder** option. This option will not report files with identical permissions as the parent folder.

4) ARKWE defaults to scanning all the sub-folders for a given folder. If you want to modify the Include sub-folders and sub-folder level options click **Edit Folder Options** button. That will show up a window as shown below:



5) Modify the folder options as required and click **OK.**

6) Select the **Validate for Errors** option for validating the folders / files based on the folder traversal option selected, before proceeding to report generation.

- **Generate report ignoring any errors found –** This option will validate the folders/ files path(s) and generate the report even if errors are encountered during the validation option.
- **Generate report only if no error were found. Send error report through e-mail–** This option will validate the folders/ files path(s) and skip the report generation if errors were encountered during the validation option. It will then email the error(s) encountered during the validation process to users.

7) You may select **Include Error Details** option for including the error information of folders / files into report data.

8) Click ***Next.***

Step 4: Delivery Options


Power Export - Standard Reports
Step 4 of 6 : Delivery Options
Select the report delivery options. You can Export and E-mail the reports using the options below. In case of export option, for each task, a sub-folder with the task name will be created under the specified export path. All selected reports will be exported to a time-stamped folder in the format "yyyy-mm-dd hh.mm.ss" under the task name folder.
Export Type:
HTML
Export
Export Path :
C:\Users\Public\Documents\ARKWE 8.x\Export
...
E-mail
To Address:
Additional E-mail Settings...
Compress the attachment
Note: This evaluation version exports / e-mails only the first 10 records.
<Back
Next>
Close

1) Change the Export or E-mail settings as necessary.
2) Use Browse button to change the export path.

Click **Additional E-mail Settings** button to specify optional e-mail settings as shown below:



Step 5: Schedule Settings



1) Enter a unique name for the task.
2) Change the Run as parameter, if necessary and set the password for the specified user.

3) Change the task schedule settings as required.
4) Click ***Next*** to proceed to the next and final step.

Step 6: Summary



1) This step displays the summary information of the task.

2) Click **Finish** to save the task details.

3) The task will be added to Windows Scheduled Tasks folder.

Schedule Permissions Built-in Reports

List of Permissions for Files

This report allows you to view the associated file permissions under a specific set of folders.

Select 

option under Power Export. This will bring up the Power Export Wizard.

Step 1: Report Selection


Power Export - Built-in Reports
Step 1 of 5 : Report Selection
Select the desired report to proceed. Only one report can be selected in this category.
List of permissions for specific users and groups on folders
List of permissions for folders
List of permissions for specific users and groups on files
List of permissions for files
<Back
Next>
Close

1) Select **"Permissions Reports"** from the select report category drop-down list.
2) Select the desired report. Only one report may be selected to run in a single task.

3) Click ***Next*** to proceed to the next step. You may Click **Back** button anytime to come back to a previous step.

Step 2: Shared Folder Selection


Power Export - Built-in Reports
Step 2 of 5 : Shared Folder Selection
Enter the full path of a Share or Shared Folder. Click Add From to load the list of shares, Import to import a list of UNC folder paths from a text file. Select a folder in the list below and Click Edit Folder Options to modify the default properties for scanning each folder.
Report
List of permissions for files
UNC Path:
Add
Scan Profile (Shares):
<No Profile found.>
Folder Path
Include sub-fold...
Folder level
\\RD50\ADMIN$ True All
\\RD50\ARKWE True All
\\RD50\C$ True All
\\RD50\E$ True All
\\RD50\new True All
Add From...
Import
Remove
Do not display files that have the same permissions as the parent folder
Edit Folder Options...
Include group membership information
Include SID
Validate for Errors
Include Error Details
Generate report ignoring any errors found
Generate report only if no errors were found. Send error report through e-mail
E-mail Settings
<Back
Next>
Close

1) Select the desired folder(s) for which you wish to run the permissions report.

2) You may also click **Import** button to import a list of UNC folder paths from a text file.

3) Files that have identical permissions as the parent folder would show up with "Same as parent" in User Name and/or Security fields in the report. However, if you do not want files with identical permissions as the parent folder reported, then select **Do not display files that have same permissions as the parent folder** option. This option will not report files with identical permissions as the parent folder.

4) ARKWE defaults to scanning all the sub-folders for a given folder. If you want to modify the Include sub-folders and sub-folder level options click **Edit Folder Options** button. That will show up a window as shown below:



5) Modify the folder options as required and click **OK.**

6) Select the **Validate for Errors** option for validating the folders / files based on the folder traversal option selected, before proceeding to report generation.
- **Generate report ignoring any errors found –** This option will validate the folders/ files path(s) and generate the report even if errors are encountered during the validation option.
- **Generate report only if no error were found. Send error report through e-mail –** This option will validate the folders/ files path(s) and skip the report generation if errors were encountered during the validation option. It will then email the error(s) encountered during the validation process to users.

7) You may select **Include Error Details** for including the error information of folders / files into report data.

8) Click ***Next*** to proceed to the *Next* step.

Step 3: Delivery Options


Power Export - Standard Reports
Step 4 of 6 : Delivery Options
Select the report delivery options. You can Export and E-mail the reports using the options below. In case of export option, for each task, a sub-folder with the task name will be created under the specified export path. All selected reports will be exported to a time-stamped folder in the format "yyyy-mm-dd hh.mm.ss" under the task name folder.
Export Type:
HTML
Export
Export Path :
C:\Users\Public\Documents\ARKWE 8.x\Export
...
E-mail
To Address:
Additional E-mail Settings...
Compress the attachment
Note: This evaluation version exports / e-mails only the first 10 records.
<Back
Next>
Close

1) Change the Export or E-mail settings as necessary.
2) Use Browse button to change the export path.

Click **Additional E-mail Settings** button to specify optional e-mail settings as shown below:



Step 4: Schedule Settings



1) Enter a unique name for the task.

2) Change the Run as parameter, if necessary and set the password for the specified user.

3) Change the task schedule settings as required.

4) Click **Next** to proceed to the next and final step.

Step 5: Summary



1) This step displays the summary information of the task.

2) Click **Finish** to save the task details.

3) The task will be added to Windows Scheduled Tasks folder.

7.5 Schedule Shares and Resources Built-in Reports



Click option under Power Export. This will bring up the Power Export Wizard.

Step 1: Report Selection


Power Export - Built-in Reports
Step 1 of 7 : Report Selection
Select the desired report(s) using the checkboxes given below. More than one report may be selected in this category.
Shares and Resources
List of Shares
List of Shares with permissions
<Back
Next>
Close

1) Select the report(s) using the checkboxes to the left of the reports. You may select any number of reports to run in a single task.

2) The above reports collect data on a server-basis.

3) Click Next to proceed to the next step. You may Click Back button anytime to come back to a previous step.

Step 2: Server Selection


Power Export - Built-in Reports
Step 2 of 6 : Server Selection
For each of the following reports, please select the list of servers for which you would like to generate the report. Double-click on a Report or click Add Servers. The report for each of the selected servers will be exported as a separate file.
List of Shares
List of Shares with permissions
Server Name
No Server Selected
Add Servers...
<Back
Next>
Close

1) Click **Add Servers** button to select the servers for which you wish to run the server reports selected in Step 1. This will display a window where you can select the servers you want to add. Selecting a domain will add all the servers in that domain to the report.

2) Click **OK** to apply the selected servers to the current report or click **Apply to Reports** to apply the servers to the rest of the selected server reports. The selected servers will be added to the wizard as shown below:


Power Export - Built-in Reports
Step 2 of 6 : Server Selection
For each of the following reports, please select the list of servers for which you would like to generate the report. Double-click on a Report or click Add Servers. The report for each of the selected servers will be exported as a separate file.
List of Shares
List of Shares with permissions
Server Name
PATHFINDER\RD45
PATHFINDER\RD53
PATHFINDER\RD47
PATHFINDER\RD49
PATHFINDER\RD54
PATHFINDER\RD52
Add Servers...
<Back
Next>
Close

3) Click **Next** to proceed to the next step.

Step 3: Report Criteria (Optional)


Power Export - Built-in Reports
Step 3 of 6 : Report Criteria (Optional)
You may specify a criteria for each of the following reports to filter data. Click Next to keep the current criteria as described under Criteria Description or click Edit Criteria to modify it.
Server Reports
List of Shares
List of Shares with permissions
Criteria Description:
(Share Type = 'Folder Share')
Edit Criteria ...
<Back
Next>
Close

This step allows you to apply specific conditions for filtering report data.

1) To set criteria for a report, select a report and Click **Edit Criteria** or Double Click the report.

2) The Criteria Settings window will be displayed as shown below:



3) Specify the criteria to filter the report data using the checkboxes.

4) Click **OK** in Criteria Settings window to go back to the wizard.

5) A description of the selected criteria will be displayed under Criteria Description as shown below:


Power Export - Built-in Reports
Step 3 of 6 : Report Criteria (Optional)
You may specify a criteria for each of the following reports to filter data. Click Next to keep the current criteria as described under Criteria Description or click Edit Criteria to modify it.
Server Reports
List of Shares
List of Shares with permissions
Criteria Description:
(Share Type = 'Folder Share' OR Share Type = 'Admin Share')
Edit Criteria ...
<Back
Next>
Close

6) Click **Next** to proceed to the Next step.

Step 4: Delivery Options


Power Export - Standard Reports
Step 4 of 6 : Delivery Options
Select the report delivery options. You can Export and E-mail the reports using the options below. In case of export option, for each task, a sub-folder with the task name will be created under the specified export path. All selected reports will be exported to a time-stamped folder in the format "yyyy-mm-dd hh.mm.ss" under the task name folder.
Export Type:
HTML
Export
Export Path :
C:\Users\Public\Documents\ARKWE 8.x\Export
...
E-mail
To Address:
Additional E-mail Settings...
Compress the attachment
Note: This evaluation version exports / e-mails only the first 10 records.
<Back
Next>
Close

1) Change the Export or E-mail settings as necessary.

2) Use Browse button to change the export path.

3) Click **Next** to proceed to the next step.

- Click **Additional E-mail Settings** button to specify optional e-mail settings as shown below.



Step 5: Schedule Settings



1) Enter a unique name for the task.

2) Change the Run as parameter, if necessary and set the password for the specified user.

3) Change the task schedule settings as required.

4) Click **Next** to proceed to the next and final step.

Step 6: Summary



1) This step displays the summary information of the task.

2) Click **Finish** to save the task details.

3) The task will be added to Windows Schedule Tasks and will be displayed in the Scheduled Tasks Manager Window as shown below:



7.6 Schedule Users and Groups Built-in Reports



Click option under Power Export.

Step 1: Report Selection


Power Export - Built-in Reports
Step 1 of 7 : Report Selection
Select the desired report(s) using the checkboxes given below. More than one report may be selected in this category.
Users and Groups
List of Users and Groups
List of User accounts
List of Local and Global groups
List of disabled user accounts
List of locked-out user accounts
Password settings of all user accounts (Password never expires etc.)
Members of Local Administrators group
Log on rights assigned for all accounts (Log on locally etc.)
Privileges assigned for all accounts
Group membership with nested groups
<Back
Next>
Close

1) **Select** the report(s) using the checkboxes to the left of the reports. You may select any number of reports to run in a single task.
2) The above reports collect data on a server-basis.
3) Click **Next** to proceed to the next step. You may Click **Back** button anytime to come back to a previous step.

Step 2: Server Selection


Power Export - Built-in Reports
Step 2 of 6 : Server Selection
For each of the following reports, select the list of servers for which you would like to generate the report. Double-click on a report or click Add Servers. The report for each of the selected servers will be exported as a separate file.
List of Users and Groups
List of User accounts
List of Local and Global groups
List of disabled user accounts
List of locked-out user accounts
Password settings of all user accounts (Password never exp
Members of Local Administrators group
Log on rights assigned for all accounts (Log on locally etc.)
Privileges assigned for all accounts
Group membership with nested groups
Server Name
No Server Selected
Add Servers...
<Back
Next>
Close

1) Click **Add Servers** button to select the servers for which you wish to run the server reports selected in Step 1. This will display a window where you can select the servers you want to add. Selecting a domain will add all the servers in that domain to the report.
2) Click **OK** to apply the selected servers to the current report or click **Apply to Reports** to apply the servers to the rest of the selected server reports. The selected servers will be added to the wizard as shown below:


Power Export - Built-in Reports
Step 2 of 6 : Server Selection
For each of the following reports, select the list of servers for which you would like to generate the report. Double-click on a report or click Add Servers. The report for each of the selected servers will be exported as a separate file.
List of Users and Groups
List of User accounts
List of Local and Global groups
List of disabled user accounts
List of locked-out user accounts
Password settings of all user accounts (Password never exp
Members of Local Administrators group
Log on rights assigned for all accounts (Log on locally etc.)
Privileges assigned for all accounts
Group membership with nested groups
Server Name
TREELAB\RD50
TREELAB\RD71
VSSLAB\RD05
VSSLAB\RD20
VSSLAB\RD21
VSSLAB\RD22
VSSLAB\RD26
Add Servers...
<Back
Next>
Close

3) Click **Next** to proceed to the next Step.

Step 3: Report Criteria (Optional)


Power Export - Built-in Reports
Step 3 of 6 : Report Criteria (Optional)
You may specify a criteria for each of the following reports to filter data. Click Next to keep the current criteria as described under Criteria Description or click Edit Criteria to modify it.
Server Reports
List of Users and Groups
List of User accounts
List of Local and Global groups
List of disabled user accounts
List of locked-out user accounts
Password settings of all user accounts (Password nev
Members of Local Administrators group
Log on rights assigned for all accounts (Log on locally
Privileges assigned for all accounts
Group membership with nested groups
Criteria Description:
(Account Type = 'Built-in User')
Edit Criteria ...
<Back
Next>
Close

This step allows you to apply specific conditions for filtering report data.

1) To set criteria for a report, select a report and Click **Edit Criteria** or Double Click the report.

2) The Criteria Settings window will be displayed as shown below:



3) Specify the criteria to filter the report data using the checkboxes.

4) Click **OK** in Criteria Settings window to go back to the wizard.

5) A description of the selected criteria will be displayed under Criteria Description as shown below:


Power Export - Built-in Reports
Step 3 of 6 : Report Criteria (Optional)
You may specify a criteria for each of the following reports to filter data. Click Next to keep the current criteria as described under Criteria Description or click Edit Criteria to modify it.
Server Reports
List of Users and Groups
List of User accounts
List of Local and Global groups
List of disabled user accounts
List of locked-out user accounts
Password settings of all user accounts (Password nev
Members of Local Administrators group
Log on rights assigned for all accounts (Log on locally
Privileges assigned for all accounts
Group membership with nested groups
Criteria Description:
(Account Type = 'Built-in User' OR Account Type = 'Custom User' OR Account Type = 'Local Group' OR Account Type = 'Global Group')
Edit Criteria ...
<Back
Next>
Close

6) Click **Next** to proceed to the Next step.

Step 4: Delivery Options


Power Export - Standard Reports
Step 4 of 6 : Delivery Options
Select the report delivery options. You can Export and E-mail the reports using the options below. In case of export option, for each task, a sub-folder with the task name will be created under the specified export path. All selected reports will be exported to a time-stamped folder in the format "yyyy-mm-dd hh.mm.ss" under the task name folder.
Export Type:
HTML
Export
Export Path :
C:\Users\Public\Documents\ARKWE 8.x\Export
...
E-mail
To Address:
Additional E-mail Settings...
Compress the attachment
Note: This evaluation version exports / e-mails only the first 10 records.
<Back
Next>
Close

1) Change the Export or E-mail settings as necessary.

2) Use Browse button to change the export path.

- Click **Additional E-mail Settings** button to specify optional e-mail settings as shown below.



Step 5: Schedule Settings



1) Enter a unique name for the task.

2) Change the Run as parameter, if necessary and set the password for the specified user.

3) Change the task schedule settings as required.

4) Click **Next** to proceed to the next and final step.

Step 6: Summary


Power Export - Built-in Reports
Step 6 of 6 : Summary
Click Finish to save the task details.
Task Name: Builtin User Task
Report Built-in Report
Run As: TREELAB\adminuser3
Schedule: At 04:30 PM every day, starting 3/22/2013
Report Name
Servers/Domains
Export As
Export Folder (Export Path\Task Name)
List of Users and Groups
Click here to view
HTML
C:\Users\Public\Documents\ARKWE 8.x\Export\Builtin User Task
List of User accounts
List of Local and Global groups
List of disabled user accounts
List of locked-out user accounts
Password settings of all user accounts (Password never expires
<Back
Finish
Close

1) This step displays the summary information of the task.

2) Click **Finish** to save the task details.

3) The task will be added to Windows Schedule Tasks and will be displayed in the Scheduled Tasks Manager Window as shown below:


Scheduled Tasks
Scheduled Tasks
Builtin Report Ta
Builtin Domain Ta
Builtin User Task
Task Name: Builtin User Task
Run As: TREELAB\adminuser3
Report Type: Built-in Report
Exported Files: Click here to view
Schedule: At 4:30 PM every day, starting 3/22/2013
Report Name
Servers/Domains
Export As
Export Folder (Export Path\Task Name)
List of Local and Global groups
Click here to view
HTML
C:\Users\Public\Documents\ARKWE 8.x\Export\Builtin User Task
List of disabled user accounts
Members of Local Administrators group
List of locked-out user accounts
Password settings of all user accounts (Password never expires etc.)
Log on rights assigned for all accounts (Log on locally etc.)
List of User accounts
Privileges assigned for all accounts
Edit Task...
Delete Task
Close

7.7 Schedule Domain Built-in Reports



Click option under Power Export.

This will bring up the Power Export Wizard.

Step 1: Report Selection


Power Export - Built-in Reports
Step 1 of 7 : Report Selection
Select the desired report(s) using the checkboxes given below. More than one report may be selected in this category.
Domains
List of trusted and trusting domains
List of machines with their OS and service pack
List of Windows Servers
List of Domain Controllers
List of Application Servers (IIS, Exchange Server, SQL Server etc.)
List of machines that run TCPIP services (FTP, telnet etc.)
List of machines that have auditing enabled (or disabled)
<Back
Next>
Close

1) **Select** the report(s) using the checkboxes to the left of the reports. You may select any number of reports to run in a single task.
2) The above reports collect data for the entire domain.
3) Click **Next** to proceed to the next step. You may Click **Back** button anytime to come back to a previous step.

Step 2 Domain Selection


Power Export - Built-in Reports
Step 2 of 6 : Domain Selection
For each of the following reports, select the list of domains for which you would like to generate the report. Double-click on a report or click Add Domains. The report for each of the selected domains will be exported as a separate file.
List of trusted and trusting domains
List of machines with their OS and service pack
List of Windows Servers
List of Domain Controllers
List of Application Servers (IIS, Exchange Server, SQL Serve
List of machines that run TCPIP services (FTP, telnet etc.)
List of machines that have auditing enabled (or disabled)
Domain Name
No Domain Selected
Add Domains...
<Back
Next>
Close

1) Click **Add Domains** button to select the domains for which you wish to run the domain reports selected in Step 1. This will display a window where you can select the domains you want to add.

2) Click **OK** to apply the selected domains to the current report or click **Apply to Reports** to apply the domains to the rest of the selected domain reports. The selected domains will be added to the wizard as shown below:


Power Export - Built-in Reports
Step 2 of 6 : Domain Selection
For each of the following reports, select the list of domains for which you would like to generate the report. Double-click on a report or click Add Domains. The report for each of the selected domains will be exported as a separate file.
List of trusted and trusting domains
List of machines with their OS and service pack
List of Windows Servers
List of Domain Controllers
List of Application Servers (IIS, Exchange Server, SQL Serve
List of machines that run TCPIP services (FTP, telnet etc.)
List of machines that have auditing enabled (or disabled)
Domain Name
RESEARCHLAB
TREELAB
VSSLAB
Add Domains...
<Back
Next>
Close

3) Click **Next t**o proceed to the next Step.

Step 3: Report Criteria (Optional)


Power Export - Built-in Reports
Step 3 of 6 : Report Criteria (Optional)
You may specify a criteria for each of the following reports to filter data. Click Next to keep the current criteria as described under Criteria Description or click Edit Criteria to modify it.
Domain Reports
List of trusted and trusting domains
List of machines with their OS and service pack
List of Windows Servers
List of Domain Controllers
List of Application Servers (IIS, Exchange Server, SQ
List of machines that run TCPIP services (FTP, telnet
List of machines that have auditing enabled (or disabl
Criteria Description:
(Domains = 'Trusted')
Edit Criteria ...
<Back
Next>
Close

This step allows you to apply specific conditions for filtering report data.

1) To set a criterion for a report, select a report and Click **Edit Criteria** or Double Click the report.

2) The Criteria Settings window will be displayed as shown below:



3) Specify the criteria to filter the report data using the checkboxes.

4) Click **OK** in Criteria Settings window to go back to the wizard.

5) A description of the selected criteria will be displayed under Criteria Description as shown below:


Power Export - Built-in Reports
Step 3 of 6 : Report Criteria (Optional)
You may specify a criteria for each of the following reports to filter data. Click Next to keep the current criteria as described under Criteria Description or click Edit Criteria to modify it.
Domain Reports
List of trusted and trusting domains
List of machines with their OS and service pack
List of Windows Servers
List of Domain Controllers
List of Application Servers (IIS, Exchange Server, SQ
List of machines that run TCPIP services (FTP, telnet
List of machines that have auditing enabled (or disabl
Criteria Description:
(Domains = 'Trusted' OR Domains = 'Trusting')
Edit Criteria ...
<Back
Next>
Close

6) **Click Next** to proceed to the Next step.

Step 4: Delivery Options


Power Export - Standard Reports
Step 4 of 6 : Delivery Options
Select the report delivery options. You can Export and E-mail the reports using the options below. In case of export option, for each task, a sub-folder with the task name will be created under the specified export path. All selected reports will be exported to a time-stamped folder in the format "yyyy-mm-dd hh.mm.ss" under the task name folder.
Export Type:
HTML
Export
Export Path :
C:\Users\Public\Documents\ARKWE 8.x\Export
...
E-mail
To Address:
Additional E-mail Settings...
Compress the attachment
Note: This evaluation version exports / e-mails only the first 10 records.
<Back
Next>
Close

1) Change the Export or E-mail settings as necessary.

2) Use Browse button to change the export path.

- Click **Additional E-mail Settings** button to specify optional e-mail settings as shown below.



Step 5: Schedule Settings



1) Enter a unique name for the task.

2) Change the Run as parameter, if necessary and set the password for the specified user.

3) Change the task schedule settings as required.

4) Click **Next** to proceed to the next and final step.

Step 6: Summary



1) This step displays the summary information of the task.

2) Click **Finish** to save the task details.

3) The task will be added to Windows Schedule Tasks and will be displayed in the Scheduled Tasks Manager Window as shown below:


Scheduled Tasks
Scheduled Tasks
Builtin Report Ta
Builtin Domain Ta
Task Name: Builtin Domain Task
Run As: TREELAB\adminuser3
Report Type: Built-in Report
Exported Files: Click here to view
Schedule: At 2:45 PM every day, starting 3/22/2013
Report Name | Servers/Domains | Export As | Export Folder (Export Path\Task Name)
List of trusted and trusting domains | Click here to view | HTML | C:\Users\Public\Documents\ARKWE 8.x\Export\Builtin Domain Task
List of machines with their OS and service pack | Click here to view | HTML | C:\Users\Public\Documents\ARKWE 8.x\Export\Builtin Domain Task
List of Windows Servers | Click here to view | HTML | C:\Users\Public\Documents\ARKWE 8.x\Export\Builtin Domain Task
List of Domain Controllers | Click here to view | HTML | C:\Users\Public\Documents\ARKWE 8.x\Export\Builtin Domain Task
List of Application Servers (IIS, Exchange Server, SQL Server etc.) | Click here to view | HTML | C:\Users\Public\Documents\ARKWE 8.x\Export\Builtin Domain Task
List of machines that run TCPIP services (FTP, telnet etc.) | Click here to view | HTML | C:\Users\Public\Documents\ARKWE 8.x\Export\Builtin Domain Task
List of machines that have auditing enabled (or disabled) | Click here to view | HTML | C:\Users\Public\Documents\ARKWE 8.x\Export\Builtin Domain Task
Edit Task...
Delete Task
Close

Chapter 7

8 Scan Profiles Manager

8.1 About Scan Profiles (Computers)

You can setup Scan Profiles to scan a subset of computers in the network and save these profiles for repeated use while generating reports (useful for repeatedly scanning and reporting on different subsets of computers).

You can create Scan Profiles in one of the following ways:

- Selecting specific computers in the network
- Selecting specific Windows versions
- Importing list of computers from a text file
- Importing list of IP addresses from a text file

8.2 How to Create Scan Profiles (Computers)?

The Scan Profile Dialog allows you to create or edit a Scan Profile. During edit operation, the name of a Scan Profile and its type cannot be modified. You can access the Scan Profile Dialog from the Scan Profiles Manager.

Perform the following steps to create a Scan Profile.

1) **Click New** button in the Scan Profiles Manager window. The Scan Profile dialog will show up on screen.
2) **Specify** a name for the Scan Profile. You must give a unique name for the Scan Profile.
3) **Specify** how you want to create the profile by selecting appropriate profile type. You can create Scan Profiles in one of the following ways:

A. Selecting computers from network



I. **Select computers from network option.**

II. You can type in computer name, in the format "Domain Name\Computer Name", and then click Add button to manually add it to the list. Or you may click **Add from** button to browse the network and select specific computers.

B. Selecting specific Windows versions



I. **Choose Select specific Windows version(s) option.**

II. Select one or more Windows versions. Only computers running the selected Windows version will be included in the computer list.

III. You may optionally select specific domains, from the list of domains, to include computers only from the selected domains. If you choose not to select any domains, then the Scan Profile includes all domains in the network.

NOTE:

- This type of profile is dynamic in nature, in that the list of computers are prepared at run-time; that is at report generation time.

C. Importing list of computers from a text file


Scan Profile (Computers)
You can specify a computer list by using either the Import option or by selecting computers from the network. Or you may select specific versions of Windows.
Profile Name:
Profile
Select computers from network
Select specific Windows version(s)
Import list of computers from text file
Import list of IP addresses from text file
File
C:\Users\Administrator\Desktop\WorkStationsList.txt
Note: The file should contain computer names in the format 'Domain\Computer' with each entry Click here to view a sample.
Import
Verify Imported
OK
Cancel

i. Select **Import list of computers from text file option.**

ii. Click browse ("...") button to select a file that contains the list of computers to be imported.

iii. In the "Select File" dialog that shows up, select a text (.txt) file, and then click Open.

iv. Click **Import** button to import the list of computers from the selected file.

NOTE:

- The text file should contain computer names in the format "Domain Name\Computer Name" (both Domain and Computer name should be a NETBIOS name) with each entry in a separate line as shown below:



- Only valid entries of the form "Domain Name\Computer Name" will be imported, and invalid entries will be ignored. Please note that the domain specified will be matched with the domain name to which the computer belongs. The computer entry will be ignored either if the domain name

does not match or if an error occurs retrieving the domain name. To view the list of entries imported, click **Verify Imported List button.** The list of computer names imported will be displayed as shown below:



- Changes to the external text file will not automatically be reflected in the Scan Profile. You need to edit the Scan Profile and re-import the updated computer list from the file.

D. Importing list of IP addresses from a text file


Scan Profile (Computers)
You can specify a computer list by using either the Import option or by selecting computers from the network. Or you may select specific versions of Windows.
Profile Name:
Research Computers
Profile
Select computers from network
Select specific Windows version(s)
Import list of computers from text file
Import list of IP addresses from text file
File
C:\Users\Administrator\Desktop\WorkStationsList.txt
Note: The file should contain valid IP addresses with each entry in a separate
Click here to view a sample.
Import
Verify Imported
OK
Cancel

i. **Select Import list of IP addresses from text file option.**

ii. Click browse ("...") button to select a file that contains the list of IP addresses to be imported.

iii. In the "Select File" dialog that shows up, select a text (.txt) file, and then click Open.

iv. Click **Import** button to import the list of IP addresses from the selected file.

NOTE:

- The text file should contain valid IP addresses with each entry in a separate line as shown below:



- During the import process each IP address will be translated to a corresponding computer name. Hence, only valid entries will be imported. To view the list of entries imported, click **Verify Imported List** button. The list of IP addresses and their corresponding computer names will be displayed as shown below:



- Changes to the external text file will not automatically be reflected in the Scan Profile. You need to edit the Scan Profile and re-import the updated IP address list from the file.

4) Click **OK** to save the Scan Profile for later use.

8.3 How to Manage Scan Profiles (Computers)?

Click 

to launch the *Scan Profiles Manager*. The Scan Profiles Manager shows the list of Scan Profiles available.


Scan Profiles Manager (Computers)
You can setup Scan Profiles to scan a subset of computers in the network and save these profiles for repeated use.
This window lists available profiles. Click New to create a new profile. Click Edit to modify selected profile. Click Delete to delete a profile. Click Preview to view the contents of a profile.
Database Servers
Resource Serve
Win2k11 Workstations
New
Edit
Delete
Preview
About Scan Profiles
Close

The Scan Profiles Manager allows you to perform the following operations:

- Create a new Scan Profile
- Edit an existing Scan Profile
- Delete a Scan Profile
- Preview the list of computers in a Scan Profile

Create a new Scan Profile

1) To create a new Scan Profile click New
2) Follow the steps as outlined in How to create Scan Profiles?

Edit an existing Scan Profile

1) To edit a Scan Profile click Edit button in the Scan Profiles Manager. The Scan Profile Dialog will appear on the screen which will allow you to edit the selected Scan Profile.
2) During edit operation you can modify the computer list; however, you cannot modify the type of the Scan Profile.

Delete a Scan Profile

To delete a Scan Profile, select the profile you want to delete, and then click Delete button. The selected Scan Profile will be deleted permanently. Please note, that reports associated with the Scan Profile deleted may fail to run when generated.

Preview the List of Computers in a Scan Profile

To preview the list of computers in a Scan Profile, select a Scan Profile, and then click **Preview** button. The computer list will be displayed in a tree view as shown below:



The Preview window shows the list of domains and computers selected in the Scan Profile if the computer list was either imported or selected from the network. Whereas, if specific Windows versions were selected, then only the computers that match the selected Windows versions will show up. Furthermore, if specific domains were associated with the Scan Profile, then only the selected domains will show up, otherwise all the domains in the network will show up. The Preview window allows you to view what computers in the network will be included in the profile.

8.4 How to Apply Scan Profiles (Computers)?

You can apply a Scan Profile to one or more reports to restrict the list of computers during report generation. This is especially useful if you want to generate reports for a subset of computers.

This page covers the following topics with regard to usage of Scan Profiles:

- Scan Profiles and Power Export Tool (off-line report generation)
- Scan Profiles and Interactive Report Generation

Scan Profiles and Power Export Tool (off-line report generation)

You can apply a Scan Profile to one or more reports using the Power Export Tool (for off-line generation) to restrict the domain scope and to scan and collect data for a subset of computers in the network. The report data will be collected for all computers in the applied Scan Profile. However, if the applied Scan Profile becomes unavailable during report generation (likely to happen if the Scan Profile is accidentally deleted); the report data will not be collected at all and will result in an error. Furthermore, if there are no computers to be found in the Scan Profile for a domain for which the report is being generated, then the report generation will fail as well. This is likely to happen if the domain is not included in the Scan Profile or none of the computers in the domain are running the Windows version setup in the Scan Profile.

Scan Profiles and Interactive Report Generation

You may also apply a Scan Profile to reports and view the data in interactive mode. The way in which a Scan Profile is applied and the data collection methodology adopted slightly differs in interactive mode from off-line report generation mode (using Power Export Tool). The data collection methodology adopted also depends on the type of Scan Profile applied (static or dynamic) to the report.

For instance, if a Scan Profile is associated with multiple domains, in interactive mode, data will be collected only for computers that belong to the currently selected domain. On the other hand, if there are no computers to be found for the currently selected domain, in the applied profile, the report data will not be collected at all. This is likely to happen if the currently selected domain was not included in Scan Profile (if it is a static profile) or the Scan Profile includes a Windows version filter, say Windows Computers only, and the domain does not have any computers running Windows XP.

In addition, in interactive mode, there are differences on how Scan Profiles are applied to **Domain-based Reports and Server-based Reports.**

Scan Profiles and Domain-based Reports

In interactive mode, for domain-based reports, you can apply a Scan Profile by using the Scan Option Dialog. The report will be generated for the list of computers in the applied Scan Profile for the currently selected domain as mentioned earlier.

Scan Profiles and Server-based Reports

For server-based reports, you can apply a Scan Profile by clicking the

button in the report window. The Scan Profiles Manager will show up on screen, select a Scan Profile, and then click **Apply** button to apply the selected profile.

For server-based reports, however, a Scan Profile when applied reloads the tree view, in the left pane in the report window, with the list of computers in the selected Scan Profile. After a Scan Profile is applied, you can select the desired computer in the tree view in the report window to generate the report. Click the **Clear** button to clear the applied profile. This will reload tree view with the list of all domains in the network.

8.5 About Scan Profiles (Users/Groups)

You can setup Scan Profiles (Users/Groups) to scan a subset of users/groups present in computers and save these profiles for repeated use (useful for repeatedly scanning and reporting on different subsets of users and groups permissions on share folders).

- How to create Scan Profiles (Users/Groups)?
- How to manage Scan Profiles (Users/Groups)?
- How to apply Scan Profiles (Users/Groups)?

8.6 How to Create Scan Profiles (Users/Groups)?

Perform the following steps to create a Scan Profile (Users/Groups).

1) Select

from the application toolbar. This action will launch the Scan Profiles Manager (Users/Groups) dialog as shown below.


Scan Profile Manager (Users/Groups)
You can setup Scan Profiles (Users/Groups) to scan a subset of users in servers and save these profiles for repeated use.
This window lists available profiles. Click New to create a new profile. Click Edit to modify selected profile. Click Delete to delete a profile. Click Preview to view the contents of a profile.
Frequent Checks
RestrictedUsers
Roaming Users
New
Edit
Delete
Preview
Close

2) Click **new** button in the Scan Profiles Manager (Users/Groups) dialog. This action will launch the ***Scan Profiles (Users/Groups)*** Wizard as shown below.



1) Enter a name for the profile.

2) Use the Browse and Select button to enumerate users/groups from servers or Scan Profiles Computers as shown below:



3) You can enter users / groups name and add to the selected account list for creating a profile. Enter the users/groups name in 'Domain\User Name' format and click the Add button to add the entered account to the list as shown below:





5) Click **Finish** to save the Users/Groups profile for future use.

8.7 How to Manage Scan Profiles (Users/Groups)?



Click to launch the **Scan Profiles Manager (Users/Groups).** The Scan Profiles Manager (Users/Groups) shows the list of available profiles.


Scan Profile Manager (Users/Groups)
You can setup Scan Profiles (Users/Groups) to scan a subset of users in servers and save these profiles for repeated use.
This window lists available profiles. Click New to create a new profile. Click Edit to modify selected profile. Click Delete to delete a profile. Click Preview to view the contents of a profile.
Frequent Checks
RestrictedUsers
Roaming Users
New
Edit
Delete
Preview
Close

The Scan Profiles Manager allows you to perform the following operations:

- Create a new Scan Profile (Users/Groups)
- Edit an existing Scan Profile (Users/Groups)
- Delete a Scan Profile (Users/Groups)
- Preview the list of users and groups in a Scan Profile (Users/Groups)

Create a new Scan Profile (Users/Groups)

1) To create a new Scan Profile (Users/Groups) click New
2) Follow the steps as outlined in How to create Scan Profiles?

Edit an existing Scan Profile (Users/Groups)

1) To edit a Scan Profile (Users/Groups) click Edit button in the Scan Profiles Manager. The Scan Profile (Users/Group) wizard will appear on the screen which will allow you to edit the selected profile.
2) During edit operation you can modify the Users/Groups list.

Delete a Scan Profile (Users/Groups)

To delete a Scan Profile (Users/Groups), select the profile you want to delete, and then click **Delete** button. The selected Scan Profile (Users/Groups) will be deleted permanently. Please note, that reports associated with the Scan Profile (Users/Groups) deleted may fail to run when generated.

Preview the List of Users and Groups in a Scan Profile (Users/Groups)

To preview the list of users and groups in a profile, select a profile, and then click **Preview** button



The Preview window allows you to view what users and groups will be included in the profile.

8.8 How to Apply Scan Profiles (Users/Groups)?

You can apply Scan Profile (Users/Groups) to permissions reports that involve generating permissions for specific users and groups on share folders. This is especially useful, if you want to generate permissions reports for certain users and groups frequently.

The following shows permissions reports that involves specific users and groups

Report Name	Description
List of permissions for specific users and groups on folders	Reports the folder permissions assigned to specific users and/or groups on a selected set of folders.
List of permissions for specific users and groups on files	Reports the files permissions assigned to specific users and/or groups under a selected set of folders.

Scan Profiles (Users and Groups) and Permission Reports for Specific Users and Groups

You can apply a Scan Profile (Users/Groups) to permissions reports either using Power Export Tool (for off-line generation) or Interactive Report Generation .This option will useful, if permissions for certain Users and Groups need to be monitored frequently. Rather than searching for Users and Groups, adding then to account list and viewing their permissions. You can use create a subset of Users and Groups, save them as a profile, generating permissions reports for subset that of users and groups. The following shows how Scan Profiles (Users/Groups) can be applied to permission reports for specific users and groups in Interactive report generation and Power export tool.

Scan Profiles (Users/Groups) and Interactive Report Generation

Perform the following steps for applying Scan Profiles (Users/Groups) to permission reports in Interactive report generation



1) Click on under Built-in Reports in the tool bar.

2) Select any one of the permissions reports listed above and click **Next** to proceed.

3) In the next step, select the option 'Select a Scan Profiles (Users/Groups) ' as shown below.


Built-in Reports - List of permissions for specific users and groups on folders
Step 2 of 3 : Select User/Group Account(s)
Select user and/or group accounts for which you would like to view the permissions on files/folders.
Enter account name :
Add to list
Accounts from domain\server:
Browse and Select
Accounts from Scan Profiles (Users/Groups):
--Select a Profile--
Selected Accounts:
Account Name
Account Type
Remove
Reset
Back
Next
Close

- In this step the list of users and/or groups present in Scan Profile (Users/Groups) will be loaded to the selected Account list as shown below:



- In the Succeeding steps, select needed details for generating reports for selected Users and Groups.

Scan Profiles (Users/Groups) and Power Export Tool (Off-line Report Generation)

You can apply a Scan Profile (Users/Groups) to permissions reports using Power Export Tool (for off-line generation).



1) Click on button in the toolbar.

2) Select any one of the permissions reports listed above and click Next to proceed.

3) In the next step, select the option 'Select a Scan Profiles (Users/Groups)' as shown below.


Power Export - Built-in Reports
Step 2 of 6 : User/Group Selection
Select a server or a Scan Profile (Computers) or a Scan Profile (Users/Groups) to retrieve available users and groups from.
Report Name: List of permissions for specific users and groups on folders
Enter account name :
Add to list
Accounts from domain\server:
Browse and Select
Accounts from Scan Profiles (Users/Groups):
--Select a Profile--
Selected Accounts
Account Name
Account Type
Remove
Reset
<Back
Next>
Close

- In this step the list of users and groups present in Scan Profile (Users/Groups) will be loaded to the selected account list as shown below:



In the succeeding steps select needed details for generating reports for selected Scan Profile (Users/Groups).

8.9 About Scan Profiles (Shares)

You can setup Scan Profiles (Shares) to scan a subset of shares present in computers and save these profiles for repeated use (useful for repeatedly scanning and reporting on different subsets of share folders permissions).

- **How to create Scan Profiles (Shares)?**
- **How to manage Scan Profiles (Shares)?**
- **How to apply Scan Profiles (Shares)?**

8.10 How to Create Scan Profiles (Shares)?

Perform the following steps to create a Scan Profiles (Shares).

1) **Select** 

from the application toolbar. This action will launch the Scan Profiles Manager (Shares) dialog as shown below:


Scan Profile Manager (Shares)
You can setup Scan Profiles (Shares) to scan a subset of shares in servers and save these profiles for repeated use.
This window lists available profiles. Click New to create a new profile. Click Edit to modify selected profile. Click Delete to delete a profile. Click Preview to view the contents of a profile.
Frequent Scans
Sample Profile1
New
Edit
Delete
Preview
Close

2) Click **New** button in the **Scan Profiles Manager (Shares)** dialog. This action will launch the **Scan Profiles (Shares)** dialog as shown below:


Scan Profiles (Shares)
Enter the full path of a Share or Shared Folder. Click Add From to load the list of shares, Import to import a list of UNC folder paths from a text file.
Profile Name:
Sample Profile
Share/Folder UNC Path:
Add
Folder Path
Add From
Import
Remove
OK
Cancel

1) Enter a name for the profile.

2) You may type the UNC path of a folder that is not in the list, such as a folder that is not shared, and then click Add, to add it to the list as shown below:


Scan Profiles (Shares)
Enter the full path of a Share or Shared Folder. Click Add From to load the list of shares, Import to import a list of UNC folder paths from a text file.
Profile Name:
Sample Profile
Share/Folder UNC Path:
\\RD55\TestLocagroups
Add
Folder Path
Add From
Import
Remove
OK
Cancel

3) You may also import a list of UNC paths to shared and non-shared folders from a text file by using the Import button.

4) Click 'Add From' to add list of share folders from computers as shown below:





5) Click Finish to save the Shares profile for future use.

8.11 How to Manage Scan Profiles (Shares)?



Click to launch the Scan Profiles Manager (Shares). The Scan Profiles Manager (Shares) shows the list of available profiles.


Scan Profile Manager (Shares)
You can setup Scan Profiles (Shares) to scan a subset of shares in servers and save these profiles for repeated use.
This window lists available profiles. Click New to create a new profile. Click Edit to modify selected profile. Click Delete to delete a profile. Click Preview to view the contents of a profile.
Frequent Scans
Sample Profile1
New
Edit
Delete
Preview
Close

The Scan Profiles Manager allows you to perform the following operations:

- Create a new Scan Profile (Shares)
- Edit an existing Scan Profile (Shares)
- Delete a Scan Profile (Shares)
- Preview the list of Shares in a Scan Profile (Shares)

Create a new Scan Profile (Shares)

1) To create a new Scan Profile (Shares) click New

2) Follow the steps as outlined in How to create Scan Profiles?

Edit an existing Scan Profile (Shares)

1) To edit a Scan Profile (Shares) click **Edit** button in the Scan Profiles Manager. The Scan Profile (Shares) wizard will appear on the screen which will allow you to edit the selected profile.
2) During edit operation you can modify the Shares list.

Delete a Scan Profile (Shares)

To delete a Scan Profile (Shares), select the profile you want to delete, and then click Delete button. The selected Scan Profile (Shares) will be deleted permanently. Please note, that reports associated with the Scan Profile (Shares) deleted may fail to run when generated.

Preview the List of Shares in a Scan Profile (Shares)

To preview the list of shares in a profile, select a profile, and then click **Preview** button.



The Preview window allows you to view what shares will be included in the profile.

8.12 How to Apply Scan Profiles (Shares)?

You can apply Scan Profile (Shares) to permissions reports. This is especially useful, if you want to generate permissions reports for certain Shares frequently.

The following shows permissions reports that involves shares profile

List of Permissions Reports:

Report Name	Description
List of permissions for specific users and groups on folders	Reports the folder permissions assigned to specific users and/or groups on a selected set of folders.
List of permissions for folders	Reports the permissions associated with a selected set of folders.
List of permissions for specific users and groups on files	Reports the files permissions assigned to specific users and/or groups under a selected set of folders.
List of permissions for files	Reports the permissions associated with files under a selected set of folders.

Scan Profiles (Shares) and Permission Reports

You can apply a Scan Profile (Shares) to permissions reports either using Power Export Tool (for off-line generation) or Interactive Report Generation .This option will useful, if permissions for certain shares need to be monitored frequently. Rather than searching for shares, adding them to list and viewing their permissions. You can create a subset of shares, save them as a profile, generating permissions reports for them. The following shows how Scan Profiles (Shares) can be applied to permission reports in Interactive report generation and Power export tool.

Scan Profiles (Users/Groups) and Interactive Report Generation

Perform the following steps for applying Scan Profiles (Shares) to permission reports in Interactive report generation



- Click on under *Built-in Reports* in the tool bar.
- Select any one of the permissions reports listed above and click next to proceed.
- In the next step, select the option 'Select a Scan Profiles (Shares) ' as shown below:


Built-in Reports - List of permissions for folders
Step 2 of 2 : Select server(s) for Shared Folders-list
Enter the full path of a Share or Shared Folder. Click Add From to load the list of shares, Import to import a list of UNC folder paths from a text file. Select a folder in the list below and Click Edit Folder Options to modify the default properties for scanning each folder.
Share/Folder UNC Path:
Add
Scan Profile (Shares):
--Select a Profile--
Folder Path
Include sub-folders
Folder level
Add From
Import
Remove
Do not display folders that have the same permissions as the parent folder
Edit Folder Options
Include group membership information
Include SID
Back
Finish
Close

- In this step the list of shares present in Scan Profile (Shares) will be loaded to the selected account list as shown below:



- In the succeeding steps select needed details for generating reports for selected shares.

Scan Profiles (Users/Groups) and Power Export Tool (Off-line Report Generation)

You can apply a Scan Profiles (Shares) to permissions reports using Power Export Tool (for off-line generation).



- Click on button in the toolbar.
- Select any one of the permissions reports listed above and click Next to proceed.
- In the next step, select the option 'Select a Scan Profiles (Shares)' as shown below:

Power Export - Built-in Reports
Step 2 of 5 : Shared Folder Selection
Enter the full path of a Share or Shared Folder. Click Add From to load the list of shares, Import to import a list of UNC folder paths from a text file. Select a folder in the list below and Click Edit Folder Options to modify the default properties for scanning each folder.
Report
List of permissions for folders
UNC Path:
Add
Scan Profile (Shares):
--Select a Profile--
Folder Path
Include sub-fold...
Folder level
Add From...
Import
Remove
Do not display folders that have the same permissions as the parent folder
Edit Folder Options...
Include group membership information
Include SID
<Back
Next>
Close

- In this step the list of shares present in Scan Profile (Shares) will be loaded to the selected account list as shown below:



In the succeeding steps select needed details for generating reports for selected shares.

References

8.13 Troubleshooting

If and when a problem arises, please forward the following information to support@vyapin.com to revert back to you with a solution. These files will be available where ARKWE is installed.

Error Log File

E.g., <Application Data Folder>\ARKWE 8.x\ARKWEErrorLog.log

NOTE:

<Application Data Folder> is the common area where ARKWE settings will be stored in the machine running ARKWE. The <Application Data Folder> can be found from the Help -> About screen. The default path of <Application Data Folder> is as follows:

a) Windows XP Windows 2003**-**C:\Documents and Settings\All Users\Documents

b) Windows Vista, Windows 7, Windows 8, Windows 2008, Windows Server 2012 - C:\Users\Public\Documents

8.14 How to Uninstall ARKWE?

When you uninstall ARKWE through Control Panel - Add / Remove Programs applet, Windows Installer program will remove only the application files from your machine. But, the application related files created by ARKWE remain in the computer. In order to remove ARKWE worker files completely, the uninstall wizard provides a set of cleanup options to perform the cleanup operation based your selection.

Use this wizard to cleanup the files that are created by ARKWE application selectively and uninstall ARKWE completely from the machine.

1) Launch the uninstall wizard by clicking ***Start -> Programs -> Admin Report Kit for Windows Enterprise v8.x -> Uninstall ARKWE.***

The ***ARKWE Uninstall Wizard*** dialog will be shown as below:


ARKWE Uninstall Wizard
Welcome to ARKWE Uninstall Wizard
This wizard helps you to cleanup and uninstall ARKWE completely.
ARKWE
This wizard will guide you through the steps to cleanup the files that are created by ARKWE application.
Using this wizard you can:
* Cleanup scheduled tasks.
* Cleanup ARKWE application settings
* Cleanup log files
* Cleanup Scan Profiles created by ARKWE Scan Profile Manager
* Uninstall ARKWE application
< Back
Next >
Finish
Cancel

Click ***Next*** to Proceed

2) Select required **Cleanup Options** as shown below:


ARKWE Uninstall Wizard
Step 1 of 2: Cleanup Options
Cleaning up the information based on your selection
ARKWE
Uninstall ARKWE application
Remove all application files and uninstall ARKWE application from the machine.
Uninstall ARKWE application and cleanup application settings
Remove all application files and uninstall ARKWE application from the machine. Also cleanup all scheduled tasks, log file, exported files and other reports settings.
Delete entire ARKWE database
< Back
Next >
Finish
Cancel

Click ***Next*** to Proceed.

3) Confirm the **Cleanup and/or Uninstall Process.**


ARKWE Uninstall Wizard
Step 2 of 2: Cleanup Process
Cleaning up the information based on your selection
ARKWE
Click 'Finish' button to proceed with the cleanup process or click 'Cancel' button to terminate the uninstall wizard.
< Back
Next >
Finish
Cancel

Click ***Finish*** to run cleanup and/or uninstall process. Click **Cancel** to close the wizard.

4) Once the file cleanup process is complete, the uninstall wizard will automatically run *Windows Installer* program to remove ***ARKWE*** *application* from the machine.

9 Index

(ARKWE), 1

About Built-in Reports, 51

About Power Export, 109

About Scan Profiles (Computers), 179

About Scan Profiles (Users/Groups), 189

About System Info, 79

Active Directory, 101, 102

Additional E-mail Settings, 119, 156, 166, 175

Additional Features, 95

Admin Report Kit for Windows Enterprise, 1, 209

applet, 209

Application Data, 208

ARKWE, 1, 2, 3, 6, 96, 100, 101, 103, 104, 107, 108, 109, 110, 208, 209, 211

Built-in Reports, 51, 67, 71, 75, 123, 124, 150, 160, 169, 196

Create Task, 79

CSV, 109

data warehousing, 3

Domain, 30, 169, 170

Domain Admins, 104

Domain Controllers, 104

Domains, 51, 170

Edit Task, 193

Enterprise network planning personnel, 3

Error Control, 49

Error Log File, 6, 208

evaluation/trial, 4

Hardware, 87

HIPPA., 1

How to activate the software?, 4

How to Apply Filters?, 96

How to apply Scan Profiles (Computers)?, 187

How to apply Scan Profiles (Users/Groups)?, 195

How to create Scan Profiles (Computers)?, 180

How to create Scan Profiles (Users/Groups)?, 189

How to customize fields?, 95

How to E-mail data?, 100

How to Export data?, 98

How to find data in a report?, 104

How to manage Scan Profiles (Computers)?, 185

How to manage Scan Profiles (Users/Groups)?, 193

How to Refresh data?, 98

How to scan specific servers in a domain?, 106

How to Uninstall ARKWE?, 209

How to view Built-in Permissions Reports, 51

How to view Built-in Reports for Domains?, 75

How to view Built-in Reports for Shares and Resources, 67

How to view Built-in Reports for Users and Groups, 71

How to view Current Status reports?, 93

How to view Display Configuration reports?, 90

How to view Domain information?, 30

How to view Environment Info reports?, 94

How to view Events information?, 46

How to view Hardware Configuration reports?, 87

How to view Internet Explorer Configuration reports?, 92

How to view Network Configuration reports?, 81

How to view Operating System and Hot Fixes reports?, 84

How to view Policies information?, 41

How to view Printer Configuration reports?, 86

How to view Service information?, 49

How to view Shares and Resources information?, 33

How to view Users and Groups information?, 37

Interactive Report, 187, 195

Internet Service Providers, 3

Intranets, 3

IP address, 184

IT infrastructure Managers, 1

LAN, 3

license key, 4, 5

MDB, 109

Microsoft Windows Network., 1

Operating System, 84

Permissions Reports, 51, 52, 123, 124

Power Export, 109

Power Export tool., 79, 108

Scan Profile, 107, 108, 114, 117, 180, 181, 183, 184, 185, 186, 187, 188, 189, 193, 194, 195

Scan Profiles, 179, 180, 185, 186, 187, 188, 189, 190, 193, 194, 195, 196

Scan Profiles Manager, 179

Schedule Built-in Reports, 123

Schedule Standard Reports, 112

Server-based Reports, 187, 188

Server-based Reports., 187

Shares and Resources, 33, 51, 67, 123, 150

SMTP server, 100

SMTP Server, 100

SOX, 1

Standard Reports (Working with Reports), 30

System Administrators, 1, 3

System Information, 79

System requirements, 2

Systems Audit personnel, 1

Systems management personnel, 3

Task Manager-Scheduled Tasks Manager, 110

Technical Support, 6

TIFF, 109

Troubleshooting, 208

uninstall, 209, 211

uninstall wizard, 209

Users and Groups, 37, 51, 71, 74, 123, 160, 195

WAN, 3

Windows network product developers, 3

Windows Servers, 3, 78